

Limitor - Medium Voltage

55 x 259



Intensité (A)	Tension	Cat. number sans percuteur	Ref. number sans percuteur	Cat. number avec percuteur	Ref. number avec percuteur	Cond.	
2	5500	55GD55V2	S081505C			3	
3,15	5500	55GD55V3,15	S081390C			3	
4	5500	55GD55V4	R081504C			3	
5	5500	55GD55V5	Q081503C			3	
6	5500	55GD55V6	P081502C	55GD55V6P	A081489C	3	
8	5500	55GD55V8	N081501C	55GD55V8P	Z081488C	3	
10	5500	55GD55V10	M081500C	55GD55V10P	Y081487C	3	
12	5500	55GD55V12	L081499C	55GD55V12P	X081486C	3	
16	5500	55GD55V16	K081498C	55GD55V16P	W081485C	3	
20	5500	55GD55V20	J081497C	55GD55V20P	V081484C	3	
25	5500	55GD55V25	H081496C	55GD55V25P	T081483C	3	
32	5500	55GD55V32	G081495C	55GD55V32P	S081482C	3	
40	5500	55GD55V40	F081494C	55GD55V40P	R081481C	3	
50	5500	55GD55V50	E081493C	55GD55V50P	Q081480C	3	
63	5500	55GD55V63	D081492C	55GD55V63P	P081479C	3	
80	5500	55GD55V80	C081491C	55GD55V80P	N081478C	3	
100	5500	55GD55V100	B081490C	55GD55V100P	M081477C	3	
Micro (1 contact)					MC1-5NFLEX	E092694A	1
Micro (2 contacts)					MC1-9NFLEXQ	F092695A	1

Moyenne Tension (HTA) - Taille 55 x 520 - Norme UTE EDF

Intensité (A)	Tension	Nomenclature EDF	Cat. number sans percuteur	Ref. number sans percuteur	Cat. number avec percuteur	Ref. number avec percuteur	Lot de 3 fusibles	Cond.
6,3	24	73.02.132	LOT-FR240V6,3	A210795A	LOT-FR240V6,3P	G227430A	1	3
16	24	73.02.133	LOT-FR240V16	B210796A	LOT-FR240V16P	H227431A	1	3
32	24	-	LOT-FR240V32	G226234A	LOT-FR240V32P	J227432A	1	3
43	24	73.02.134	LOT-FR240V43	C210797A	LOT-FR240V43P	K227433A	1	3
63	24	73.02.135	LOT-FR240V63	D210798A	LOT-FR240V63P	L227434A	1	3

