


LL3-DH04

LL3

FIBERS

SICK
Sensor Intelligence.



Ordering information

Type	Part no.
LL3-DH04	5326022

Other models and accessories → www.sick.com/LL3

Detailed technical data

Features

Device type	Fibers
Functional principle	Proximity system
For fiber-optic sensor	GLL170(T), WLL180, WLL80
Fiber length	2,000 mm
Fiber material	Glass
Jacket material	Stainless steel
Fiber head material	Stainless steel
Outer diameter, fiber-optic cable connection	2.2 mm
Thread diameter (housing)	M6
Fiber-optic head design	Threaded sleeve, Long end sleeve, Bendable sleeve
Array width	8.75 mm
Fiber arrangement	Multi-fiber – fiber bundle
Core structure	S: 380 x Ø 0,5 µm R: 380 x Ø 0,5 µm Multi-fiber – fiber bundle
Angle of dispersion < 60°	No
Compatibility with infrared light (1,450 nm)	Yes ¹⁾
Application	Heat-resistant (≥100 °C)
Diameter/thread size from 2 mm taper	≥ 2.8 mm
Length of taper	≥ 60 mm
Diameter of taper	≥ 2.8 mm
Highly flexible/elastic fibers (bend radius 1–4 mm)	No
Adapter end sleeves required	No
Angle of dispersion	60°
Integrated lens	No
Minimum bend radius of end sleeve	10 mm
Minimal object diameter	0.02 mm ²⁾
Included with delivery	Mounting, 2 x M6 hexagon nut, 1 x washer
Compatibility tip adapters	No

¹⁾ Reduced sensing ranges possible when using a fiber-optic amplifier with infrared light.

²⁾ Minimum detectable object was determined at optimum measuring distance and optimum setting.

Mechanics/electronics

Bend radius, fibre-optic cable	25 mm
Bend radius, end sleeve	10 mm
Ambient operating temperature	-30 °C ... +350 °C

Classifications

ECLASS 5.0	27270905
ECLASS 5.1.4	27270905
ECLASS 6.0	27270905
ECLASS 6.2	27270905
ECLASS 7.0	27270905
ECLASS 8.0	27270905
ECLASS 8.1	27270905
ECLASS 9.0	27270905
ECLASS 10.0	27270905
ECLASS 11.0	27270905
ECLASS 12.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
ETIM 7.0	EC002651
ETIM 8.0	EC002651
UNSPSC 16.0901	39121528

Sensing ranges with WLL80

Operating mode 16 µs	120 mm
Operating mode 70 µs	300 mm
Operating mode 250 µs	500 mm
Operating mode 500 µs	595 mm
Operating mode 1 ms	665 mm
Operating mode 2 ms	900 mm
Operating mode 8 ms	1,090 mm

Sensing ranges with WLL180T

Operating mode 16 µs	65 mm
Operating mode 70 µs	225 mm
Operating mode 250 µs	500 mm
Operating mode 2 ms	1,000 mm
Operating mode 8 ms	1,060 mm
Note	Sensing ranges related to fiber-optic sensors with type of light: visible red light

Sensing ranges with GLL170

Operating mode 250 µs	150 mm
------------------------------	--------

Sensing ranges with GLL170T


Operating mode 50 µs	150 mm
-----------------------------	--------

Operating mode 250 μ s

360 mm


Dimensional drawing (Dimensions in mm (inch))

LL3-DH04



Recommended accessories

Other models and accessories → www.sick.com/LL3

	Brief description	Type	Part no.
Device protection (mechanical)			
	Metal protection hose for LL3-Fibers with M6 threaded head; length 1000 mm, stainless steel, 1 pieces	BEF-LL3M61000	5331291
	Metal protection hose for LL3-Fibers with M6 threaded head; length 500 mm, stainless steel, 1 pieces	BEF-LL3M6500	5331290

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com