

PRODUCT-DETAILS

6819/68-183-500

Presence Detector 8 m



### Informations générales

Extension du type de produit	6819/68-183-500
Code de produit	2CKA006800A2785
EAN	4011395218150
Description courte	Presence Detector 8 m
Description longue	Slave presence detector for extension of the detection range of master presence detectors. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 6.5 m, walking persons: up to Ø 8 m. Visible height 23 mm. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Surveillance density: 48 sectors with 496 switching segments. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.

### Installation

Instructions et manuels	No document needed
-------------------------	--------------------

### Technique

Fiche produit, informations techniques	2CKA001473B9577
Fonction	Extension unit
Tension nominale (U <sub>r</sub> )	230 V AC
Auxiliary Voltage AC/DC	110 V AC/DC 230 V AC/DC

Type de tension	AC
Fréquence assignée (f)	50 / 60 Hz
Power Loss	0.3 W
Plage de mesure	8 m
Number of Switching Zones	496
Type de raccordement	Plug Clamp
Type de montage	Built-in
Sensor Type	Passive infrared
Finition de surface	Surface protection: Lacquered Surface finishing: Matt
Matériau	Thermoplastic
Type d'encastrement	Ceiling
Model Number	Presence detector
RAL Number	RAL 9006 - Aluminium blanc
Couleur	aluminium silver
Application Function	Electrical Load and Light Control

## Environnement

Température de l'air ambiant	Operation -5 ... +45 °C
Indice de protection	IP40
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CKA200000E6528
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Dimensions

Produit Largeur Net	94 mm
Produit Hauteur Net	94 mm
Produit Longueur Net	72 mm
Poids net	128.1 g
Profondeur d'encastrement (t <sub>2</sub> )	49 mm

## Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E0710
--------------------------------	-----------------

## Classifications

ETIM 8	EC000133 - Movement sensor complete
ETIM 9	EC000133 - Movement sensor/presence detector complete
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27144007

---

## Accessories

---

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006800A2771	Presence Detector 8 m 200 W	6817/62-183-500	1	piece
2CKA006800A2769	Presence Detector 12 m 2300 W	6819/30-183-500	1	piece
2CKA006800A2775	Presence Detector 12 m 2300 W	6819/31-183-500	1	piece
2CKA006800A2773	Presence Detector 12 m 200 W	6817/32-183-500	1	piece
2CKA006800A2777	Presence Detector 12 m 200 W	6817/33-183-500	1	piece
2CKA006800A2781	Presence Detector 12 m DALI 1380 W	6819/35-183-500	1	piece
2CKA006800A2765	Presence Detector	6889/30-24-500	1	piece
2CKA006899A2304	Protection Cover	6898	1	piece

---

---

## Catégories

---

Produits basse tension → Wiring Accessories - StandAlone Electronics → Presence Detector → Professional Series

