



| | | | |
|--|---|-----------------|--------------|
| Product designation | Illuminated selector switch actuator - 3 position | | |
| Product type designation | LPCSL1315+LPXAU120 | | |
| General characteristics | | | |
| Colour | Yellow | | |
| Type of positions | Selector switch | | |
| IEC degree of protection | IP66, IP67 and IP69K | | |
| Electrical characteristics | | | |
| Rated insulation voltage U_i IEC/EN | V | 690 | |
| IEC Conventional free air thermal current I_{th} | A | 10 | |
| Supply voltage (AC) | V | 12...30 | |
| Supply voltage (DC) | V | 12...30 | |
| Conductivity | 1mA 5V | | |
| UL/CSA and IEC/EN 60947-5-1 designation | A600 Q600 | | |
| Operating current AC15 | | | |
| | 12V | A | 6 |
| | 24V | A | 6 |
| | 48V | A | 6 |
| | 120V | A | 6 |
| | 240V | A | 3 |
| | 400V | A | 1.9 |
| | 480V | A | 1.5 |
| | 500V | A | 1.4 |
| | 600V | A | 1.2 |
| Operating current DC13 | | | |
| | 12V | A | 3 |
| | 24V | A | 3 |
| | 48V | A | 1.5 |
| | 125V | A | 0.55 |
| | 250V | A | 0.27 |
| | 440V | A | 0.15 |
| | 500V | A | 0.13 |
| | 600V | A | 0.1 |
| Contact resistance | mΩ | | ≤20 |
| Operations | | | |
| Electrical life | hours | 100000 | |
| Mechanical features | | | |
| Mechanical life | cycles | 1000000 | |
| Terminals screw | Screw | | |
| Conductor section | IEC | | |
| | max | mm ² | 1 or 2 / 2.5 |
| Mounting adapter | LPXAU120 | | |
| UL technical data | | | |
| UL degree of protection | Type1, 2, 3R, 4, 4X, 12, 12K | | |
| Ambient conditions | | | |
| Temperature | Operating temperature | | |
| | min | °C | -25 |
| | max | °C | +70 |
| | Storage temperature | | |
| | min | °C | -40 |
| | max | °C | +85 |
| Certifications and compliance | | | |
| Compliance | CSA C22.2 n° 14 | | |
| | IEC/EN/BS 60947-1 | | |
| | IEC/EN/BS 60947-5-1 | | |
| | UL508 | | |
| Certificates | | | |

KIT PLASTIC ILLUMINATED SELECTOR SWITCH ACTUATOR, 3 POSITION, 1 > 0 < 2.
YELLOW WITH MOUNTING ADAPTER AND 2 CONTACT ELEMENTS, 1NO+1NC. SCREW
TERMINATION. LED INTEGRATED LAMP-HOLDER, STEADY LIGHT, 12...30VAC/DC

CCC

cULus

EAC

RINA
