



















**Attache-câbles SL-HT**  
pour usage en extérieur et/ou à températures  
plus élevées  
PA 6.6 noir H.T.



**SES-QUICK**  
-40 à +110°C




• **Attaches SL HT**  
résistant aux U.V. - crantage intérieur

type	code article	dimensions long. x largeur mm	Ø de serrage maxi. (mm)	résistance à la traction daN	
85/24 SL HT-M	0186 0110 010	85 x 2,4	16	8	1000
85/24 SL HT-C	0186 0111 010	85 x 2,4	16	8	100 
100/25 SL HT-M	0186 0120 010 *	100 x 2,5	20	8	1000
100/25 SL HT-C	0186 0121 010	100 x 2,5	20	8	100 
150/26 SL HT-M	0186 0122 010	150 x 2,6	40	8	1000
150/26 SL HT-C	0186 0123 010	150 x 2,6	40	8	100 
200/26 SL HT-M	0186 0180 010 *	200 x 2,6	50	8	1000
200/26 SL HT-C	0186 0181 010	200 x 2,6	50	8	100 
145/34 SL HT-M	0186 0130 010 *	145 x 3,4	35	13	1000
145/34 SL HT-C	0186 0131 010	145 x 3,4	35	13	100 
210/34 SL HT-M	0186 0142 010	210 x 3,4	55	13	1000
210/34 SL HT-C	0186 0143 010	210 x 3,4	55	13	100 
300/36 SL HT-M	0186 0232 010	295 x 3,6	76	13	1000
300/36 SL HT-C	0186 0233 010	295 x 3,6	76	13	100 
370/36 SL HT-C	0186 0242 010	370 x 3,6	102	13	100 
160/46 SL HT-M	0186 0124 010	160 x 4,6	38	22	1000
160/46 SL HT-C	0186 0125 010	160 x 4,6	38	22	100 
185/46 SL HT-M	0186 0140 010	185 x 4,6	47	22	1000
185/46 SL HT-C	0186 0141 010	185 x 4,6	47	22	100 
250/46 SL HT-M	0186 0126 010	250 x 4,6	60	22	1000
250/46 SL HT-C	0186 0127 010	250 x 4,6	60	22	100 
300/46 SL HT-M	0186 0146 010	300 x 4,6	83	22	1000
300/46 SL HT-C	0186 0147 010	300 x 4,6	83	22	100 
380/47 SL HT-C	0186 0150 010	380 x 4,7	109	22	100 
180/76 SL HT-C	0186 0132 010	180 x 7,6	36	54	100 
240/76 SL HT-C	0186 0144 010	240 x 7,6	50	54	100 
300/76 SL HT-C	0186 0148 010	300 x 7,7	76	54	100 
365/76 SL HT-C	0186 0160 010	365 x 7,6	100	53	100 
550/90 SL HT-C	0186 0163 010	550 x 8,9	155	79	100
780/90 SL HT-C	0186 0162 010	775 x 8,9	230	79	100



\* livré par 10 bottes de 100 pcs.

 livré en sachet muni d'un trou européen de suspension.