

**Illuminated selector switch actuator, RMQ-Titan, maintained, 3 positions,
2 NO, green, Blister pack for hanging**



Part no. M22-WRLK3-G-2K10LED-BVP
110925
EL Number 4356248
(Norway)

Product name	Eaton Moeller® series M22 Illuminated selector switch actuator
Part no.	M22-WRLK3-G-2K10LED-BVP
EAN	4015081104543
Product Length/Depth	50 millimetre
Product height	80 millimetre
Product width	50 millimetre
Product weight	0.049 kilogram
Compliances	Contact Manufacturer
Certifications	CE
Product Tradename	M22
Product Type	Illuminated selector switch actuator
Product Sub Type	None
Catalog Notes	Blister pack for hanging. Can be ordered using a single article no. Complete practical solution.
Bezel color	Titanium
Bezel material	Plastic
Fitted with:	Front ring
Degree of protection	NEMA 4X
Degree of protection (front side)	IP66
Opening diameter	22.5 mm
Product category	RMQ-Titan
Suitable for	Illumination
Used with	Modular pushbutton
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Connection to SmartWire-DT	No
Actuator color	Green
Actuator function	Switching function latching
Actuator type	Toggle
Number of switch positions	3
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdis	0 W
Heat dissipation per pole, current-dependent Pvid	0.11 W
Rated operational current for specified heat dissipation (In)	6 A
Static heat dissipation, non-current-dependent Pvs	0.45 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire

10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for selector switch (EC000222)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for selector switches (ecl@ss10.0.1-27-37-12-13 [AKF031014])		
Number of switch positions		3
Type of control element		Toggle
Suitable for illumination		Yes
Colour control element		Green
Colour indicator light cap		Green
Construction type lens		Round
Hole diameter	mm	22.5
Width opening	mm	0
Height opening	mm	0
Switching function latching		Yes
Spring-return		No
With front ring		Yes
Material front ring		Plastic
Colour front ring		Titanium
Degree of protection (IP), front side		IP66
Degree of protection (NEMA)		4X