

PRODUCT-DETAILS

CM-SRS.11P

CM-SRS.11P Current monitoring relay 1c/o, B-C=3mA-1A RMS, 110-130VAC



Informations générales

Extension du type de produit	CM-SRS.11P
Code de produit	1SVR740841R0200
EAN	4016779852524
Description courte	CM-SRS.11P Current monitoring relay 1c/o, B-C=3mA-1A RMS, 110-130VAC
Description longue	<p>The CM-SRS.11P is a single-functional current monitoring relay from the CM single-phase monitors range. This monitoring relay operates with a rated control supply voltage of 110 - 130 V AC and has a 1 c/o (SPDT) output contact rated at 250 V / 4 A. It provides a RMS measuring principle for DC and AC currents with 3 measuring ranges: 3-30 mA, 10-100 mA and 0.1-1 A and works according to the open-circuit principle. The CM-SRS.11P is configurable for over- or undercurrent monitoring, the hysteresis is adjustable within a range of 3 to 30 % of the threshold value. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.</p>

Commande

EAN	4016779852524
Quantité minimum	1 pièce
Code douanier	85364900

Downloads Préférés

Fiche produit, informations techniques	2CDC112167D0201
--	-----------------

Instructions et manuels	1SVC730720M1000 1SVC730720M0000
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Produit Largeur Net	22.5 mm
Produit Hauteur Net	85.6 mm
Produit Longueur Net	103.7 mm
Poids net	0.153 kg

Technique

Fonction	Over- or undercurrent monitoring
Plage de mesure	3 ... 30 mA 10 ... 100 mA 0.1 ... 1 A
Rated Control Supply Voltage (U_s)	110 ... 130 V AC
Sortie	1 c/o (SPDT) contact
Type de borne	Screwless Terminals
Rated Operational Current AC-12 (I_{θ})	(230 V) 4 A
Courant assignée d'emploi AC-15 (I_{θ})	(230 V) 3 A
Rated Operational Current DC-12 (I_{θ})	(24 V) 4 A
Courant assignée d'emploi DC-13 (I_{θ})	(24 V) 2 A
Minimum Switching Capacity	24 V 10 mA
Tension assignée de tenue aux chocs (U_{imp})	Measuring Circuit / Output Circuit 6 kV Output Circuit 1 / Output Circuit 2 4 kV Supply Circuit / Measuring Circuit 6 kV Supply Circuit / Output Circuit 4 kV
Tension assignée d'isolement (U_i)	Measuring Circuit / Output Circuit 600 V Output Circuit 1 / Output Circuit 2 250 V Supply Circuit / Measuring Circuit 600 V Supply Circuit / Output Circuit 250 V
Indice de protection	Housing IP50 Terminals IP20
Catégorie de Surtension	III
Degré de pollution	3
Dispositif de protection contre les courts-circuits	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Durabilité mécanique	30000000 cycle
Connecting Capacity	Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 2x 0.5 ... 1.5 mm ²
Wire Stripping Length	8 mm
Type d'encastrement	1 ... 6
Montage sur rail DIN	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Normes et standards	CAN/CSA C22.2 No. 14 IEC/EN 63000 IEC/EN 60255-27

IEC/EN 61000-6-2
IEC/EN 61000-6-3
UL 508

Technique UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG
Pilot Duty UL/CSA	B300
Flammability According to UL94	V-0

Environnement

Température de l'air ambiant	Operation -20 ... +60 °C Storage -40 ... +85 °C
Altitude de fonctionnement maximale autorisée	Without Derating 2000 m
REACH Declaration	1SVD981001-4501
Informations RoHS	1SVD981013-00
Statut RoHS	Following EU Directive 2011/65/EU

Valeur Circulaire

Instructions relatives à la fin de vie	1SAC200290H0001
--	-----------------

Certificats et Déclarations (Numéro de document)

CB Certificate	CB_DK-28255-UL
CQC Certificate	CQC2007010303243843
Certificat ecULus	cULus508_20120203-E140448
Declaration of Conformity - CCC	2020980303000196
Déclaration de Conformité - CE	1SVD981013-00
Declaration of Conformity - UKCA	1SVD981013-10
DNV GL Certificate	DNV_GL_TAA0000293
EAC Certificate	EAC_RU_C-DE.ME77.B.03424

Emballage

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	97 mm
Emballage Niveau 1 Longueur	30 mm
Emballage Niveau 1 Hauteur	109 mm
Emballage Niveau 1 Poids	0.175 kg

Emballage Niveau 1 EAN

4016779852524

Classifications

Code de classification d'objet	B
ETIM 7	EC001440 - Current monitoring relay
ETIM 8	EC001440 - Current monitoring relay
ETIM 9	EC001440 - Current monitoring relay
eClass	V11.0 : 27371802
UNSPSC	39122332
E-Number (Finland)	2712301
E-Number (Sweden)	3860651

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Relais électroniques → Contrôle de réseau monophasé

