

## Features

Use: Outdoor  
Type of installation: INCASSO A PAVIMENTO  
Emission: INDIRECT  
Optics: SPOT  
Beam: 15°  
Colour: BRUSHED STAINLESS AISI 316  
Dimming: ON/OFF  
Emergency: NO  
L: 95mm  
A: 95mm  
H: 115mm  
Warranty: 5 years  
Weight: 0.545kg

## Tech data

Luminaire input power: 5W  
Luminaire luminous flux: 353lm  
IP: 67  
Insulation class: I  
Supply voltage: 220-240V 50/60Hz

## Source

Light source: LED  
Source power: 5W  
Colour temperature: 3000K  
CRI: >90  
LED lifespan: 30000h L70 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-13

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)


# ZENIT

111303.09

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

## MOUNTING ACCESSORIES

---



ZENIT: CASSAFORMA

111305.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.