



|                                      |  |    |     |                      |
|--------------------------------------|--|----|-----|----------------------|
| Product designation                  |  |    |     | TERMINALS PROTECTION |
| Product type designation             |  |    |     | CN                   |
| <b>Ambient conditions</b>            |  |    |     |                      |
| Operating temperature                | min  | °C | -5  |                      |
|                                      | max  | °C | 55  |                      |
| <hr/>                                |  |    |     |                      |
| Storage temperature                  | min  | °C | -30 |                      |
|                                      | max  | °C | 80  |                      |
| <b>Mechanical features</b>           |  |    |     |                      |
| Weight                               |  |    | g   | 2                    |
| <b>Certifications and compliance</b> |  |    |     |                      |
| Compliance                           | IEC/EN 60947-1   |    |     |                      |
|                                      | IEC/EN 60947-4-1   |    |     |                      |
|                                      | IEC/EN 60947-5-1   |    |     |                      |
|                                      | IEC/EN 61095   |    |     |                      |
| <hr/>                                |  |    |     |                      |
| Certificates                         | EAC  |    |     |                      |
| <b>ETIM classification</b>           |  |    |     |                      |
| ETIM 8.0                             | EC002498 - Accessories/spare parts for low-voltage switch technology |    |     |                      |