



### Caractéristiques de la gamme

• Insaver Slim G2 UGR19 205 20W 2350lm 830 DALI - Downlight LED rond avec dissipateur aluminium alliant confort visuel et performances élevées. Lentilles en polycarbonate spécialement conçues avec réflecteur en aluminium permettant un éblouissement de niveau UGR<19. Température de couleur (CCT) 3000K, IRC80. Flux lumineux sortant 2350lm. Driver Dali fourni compatible avec bouton poussoir. Puissance consommée 20W. Efficacité lumineuse 124lm/W. SDCM:3. Durée de vie (L80) : 90.000h. IP44, IK07. Classe II. 850°C. Diamètre 220mm. Hauteur 60m...

### CIBSE TM66

Result			
Category	Points Scored	Maximum possible points	Assessment
Product design	60	134.0	1.8
Manufacturing	17.1	46.5	1.5
Materials	0	24.0	0
Ecosystem	18	43.0	1.7
Overall performance	95.1	247.5	1.25

  

How to analyse the score	
0.0 to 0.5	Very poor circular economy performance
0.5 to 1.5	Some circular economy functionality
1.5 to 2.5	Definite/substantial progress to circularity
2.5 to 4.0	Excellent circularity

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy