



Product designation			Variable speed drives
Product type designation			VLB3
General characteristics			
Rated power supply voltage			400...480VAC 50/60Hz
Rated output voltage	VAC		Three-phase 0... 480VAC 0-599Hz
Rated output current	A		2.4
Rated output power	kW		0.75
Rated output power	HP		1 (heavy load)
EMC filter			Built-in EMC suppressor cat. C1/C2
Technical features			
Input type			Three-phase
Rated mains voltage	VAC		400...480
Operating mains voltage range	VAC		340...528
Rated mains frequency	Hz		50/60
Operating mains frequency range	Hz		45...65
Rated mains current without mains choke			3.3
Rated mains current with mains choke			2.6
Output type			Three-phase
Output voltage range	VAC		0...480
Output frequency range	Hz		0...599
Current overload	%/s		150% for 60s; 200% for 3s
Apparent output power			1.6 (heavy load)
Power loss			4kHz: 32W (heavy load)
Brake chopper			Yes
Switching frequency			2...16kHz
Max motor cable length			
	Shielded		
		Without EMC category	m
		Category C1	m
		Category C2	m
		Category C3	m
	Unshielded		
			50m / 100m (40°C max, switching frequency 4kHz max)
			3
			20
			20

Without EMC category m 100m / 150m
(40°C max,
switching
frequency 4kHz
max)

Functions


Motor control modes	V/f linear, quadratic torque, sensorless vector control, ECO mode, servo control with encoder feedback, multipoint V/f curve, V/f closed loop control with encoder feedback, torque setpoint, sensorless
Speed reference signals	External potentiometer 0...10kΩ Voltage signals: 0... 10VDC or -10... +10VDC Current signals: 0/4... 20mA Buttons on front keyboard Door-mount installation kit 15 preset speeds via digital inputs Motor potentiom
3-wire control	Yes
S-shape curves	Yes
Slip compensation	Yes
Flying restart	Yes
Access to DC bus	Yes
DC braking	Yes
DC injection at start	Yes
PID control	Yes, with sleep and rinse function
Sequencer (programmable frequency/time cycles)	Yes
Preset speeds	Yes
Motorpotentiometer	Yes
Different parameter configuration sets	Yes
Parameters changeover function	Yes
Favorite parameters menu	Yes
Autotuning	No
Safe torque Off (STO) safety function	Optional
PTC probe input	Yes

Protections	Overcurrent Output short circuit and earth/ground leakage Overvoltage Undervoltage Phase loss Motor heat overload (i2t) Overspeed Speed reverse
Special funct.	Multi-pump PID control (1 main pump frequency regulated + 2 auxiliary pumps activated in direct mode in case of necessity)
Input and Output	
Number of digital input	Nr. 5
Digital input type	Selectable PNP or NPN logic
Number of digital output	Nr. 2
Digital output arrangement	1 relay output with changeover contact (C/O-SPDT) + 1 digital output
Output contacts ratings	Relay output: 3A 250VAC Digital output: 100mA max 30VDC
Number of analog input	Nr. 2
Analog input type	Configurable 0/2...10VDC, -10...+10VDC, 0...5VDC, 0/4...20mA
Number of analog output	Nr. 1
Analog output type	configurable as 0...10VDC, 0...5VDC, 2...10VDC, 0/4...20mA
Ambient conditions	
Temperature	
Operating temperature	
	min °C -10
	max °C +55

			switching frequency 2 or 4kHz: 2.5%/°C over 45°C
	Current derating		switching frequency 8 or 16kHz: 2.5%/°C over 40°C
Storage temperature	min	°C	-25
	max	°C	+60
Relative humidity		%	5...95% (with no condensing)
Max altitude		m	4000m (over 1000m derate the rated current by 5%/1000m)
Maximum Pollution degree			2
Overvoltage category			III up to 2000m altitude (II above 2000m)

Housing			
Installation position			Vertical
IP degree of protection			IP20
Dimensions (W x H x D)	mm		60 x 214 x 130
Weight	Kg		1

Dimensions



Certifications and compliance

Compliance	CSA 22.2 n°274
	EN 61800-5-1
	UL61800-5-1

Certificates	CSA
	cULus
	EAC

RCM

ETIM classification

ETIM 8.0

EC001857 -
Frequency
converter =< 1 kV