

PRODUCT-DETAILS

TY200-18X-M

80N UV CABLE TIE 200MM OEM



Informations générales

| | |
|------------------------------|---|
| Extension du type de produit | TY200-18X-M |
| Code de produit | 7TCG054360R0435 |
| EAN | 5415022524376 |
| Description courte | 80N UV CABLE TIE 200MM OEM |
| Description longue | "Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 115 Degrees Celsius, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/IEC 62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 200mm, Width of 2.5mm, Thickness of 1.1mm , Tensile Strength Rating of 80 Newtons, 1000 Pack" |

Commande

| | |
|-----------------|---------------|
| EAN | 5415022524376 |
| UPC | 786210362342 |
| Pays d'origine | China (CN) |
| Unité de mesure | each |

Emballage

| | |
|----------------------------|--------------------|
| Emballage Niveau 1 Unités | 1000 pièce |
| Emballage Niveau 1 Largeur | 10.24 in 260 mm |

| | |
|--------------------------------|--------------------|
| Emballage Niveau 1 Hauteur | 1.77 in 45 mm |
| Emballage Niveau 1 Longueur | 12.2 in 310 mm |
| Emballage Niveau 2 Unités | 10000 pièce |
| Emballage Niveau 2 Largeur | 15.75 in 400 mm |
| Emballage Niveau 2 Hauteur | 4.72 in 120 mm |
| Emballage Niveau 2 Longueur | 19.69 in 500 mm |

Informations Supplémentaires

| | |
|---------------------|--|
| Marque / Étiquette | Ty-Fast |
| Bundle Diameter | 52.5 mm 2.067 in |
| Couleur | Black |
| Effective Date | 20220125 |
| Lock Type | Plastic Pawl |
| Groupe de produit | CABLE TIES AND ACCESSORIES |
| Type de produit | PLASTIC CABLE TIE |
| Type de produit | General Purpose |
| Fonctions spéciales | "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool" |
| Normes et standards | UL E49405 |
| Tensile Strength | 80 N 18 lb |
| Thickness | 1.1 mm 0.043 in |

Certificats et Déclarations (Numéro de document)

| | |
|--|-----------|
| Fiche produit, informations techniques | TDS000751 |
|--|-----------|

Classifications

| | |
|--|----------------------|
| ETIM 6 | EC000046 - collier |
| ETIM 7 | EC000046 - Cable tie |
| ETIM 8 | EC000046 - Cable tie |
| UNSPSC | 39121703 |
| Code de catégorie granulaire IDEA (IGCC) | 5034 >> Cable ties |

Catégories

Produits basse tension → Produits d'installation → Gestion des câbles et connectivité → Cable Ties

