LPFQ105




electric PUSH-PUSH BUTTON ACTUATOR Ø30MM PLATINUM SERIES FLAT METAL, FLUSH. PUSH ON-PUSH OFF, YELLOW



| Product designation | | | | Push-push button actuators | |
|---------------------------------------|-----------------------|--|-------|----------------------------|---------------------------------------|
| Product type designation | | | | LPFQ10 | |
| General characteristics | | | | | |
| Colour | | | | | Yellow |
| Type of positions | | | | | Flush pushbutton. Push on-push off |
| Material | | | | Aluminium and zinc alloy | |
| IEC degree of protection | | | | IP66, IP67 and IP69K | |
| Mechanical features | | | | | |
| Operating force | | | kg-lb | <0.5Kg / 1.1lb | |
| Mechanical life - Push-Push actuators | | | | cycles | 500000 |
| Fixing | | | | | Without mounting adapter |
| Mounting adapter | | | | | LPXAU120M |
| UL technical data | | | | | |
| UL degree of protection | | | | | Type1, 2, 3R, 4, 4X, 12, 12K |
| Ambient conditions | | | | | |
| Temperature | | | | | |
| | Operating temperature | | | | |
| | | | min | °C | -25 |
| | | | max | °C | +70 |
| | Storage temperature | | | | |
| | | | min | °C | -40 |
| | | | max | °C | +85 |

Dimensions



Certifications and compliance

| Compliance | |
|---------------------|---------------------|
| | CSA C22.2 n° 14 |
| | IEC/EN/BS 60947-1 |
| | IEC/EN/BS 60947-5-1 |
| | UL508 |
| Certificates | |
| | cULus |
| ETIM classification | |
| | |



LPFQ105 electric PUSH-PUSH BUTTON ACTUATOR Ø30MM PLATINUM SERIES FLAT METAL, FLUSH. PUSH ON-PUSH OFF, YELLOW

ETIM 8.0

EC000221 -Front element for push button