

P-30 STRIP LED

105889.01











Features

Use: Indoor Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED Emission: ADJUSTABLE Optics: SPOT Beam: 20° Colour: WHITE Dimming: ON/OFF Emergency: NO L: 800mm A: 31mm Made in: ITALY Warranty: 5 years

<u>()()(</u>

ITALIAN LIGHTING DESIGN SINCE 1948

Tech data

Luminaire input power: 28W Luminaire luminouse flux: 2108lm IP: 20 Insulation class: I Supply voltage: 220-240V 50/60Hz SELV: Sì

Source

Light source: LED Source power: 24W Colour temperature: 4000K CRI: >90 Colour tolerance: 2 Step MacAdam LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 1Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

View more product info



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com Company subject to the management and coordination by SLV Gmbh