



Product designation	Switching power supplies		
Product type designation	PSL3		
<b>Input characteristics</b>			
Input type	Three-phase		
Rated supply voltage AC	VAC	Multivoltage 400...500	
Operating range			
AC	min	VAC	340
	Max	VAC	575
DC	min	VDC	480
	Max	VDC	820
Rated frequency		Hz	50/60
Operational frequency	min	Hz	47
	max	Hz	63
Current consumption Max		mA	1400
PFC			0.65
Insulation voltage Input/Output	AC	VAC	3000
	DC	VAC	4242
Internal fuse (250VAC)	T3 15A 500VAC		
<b>Output characteristics</b>			
Rated output voltage DC		VDC	24
Voltage trimming (potentiometer) DC	min	VDC	22.5
	Max	VDC	28.5
Rated output current		A	20
Rated output power		W	480
Temperature coefficient		%/°C	±0.03
Line adjustment		%	±1
Load adjustment		%	±1
Efficiency		%	90
Overload protection			110...135%
Short-circuit protection			Fold forward
Ripple & noise		mV	100
Parallel connection		Nr.	2
<b>Indications</b>			
LED indicator for power on			Yes
LED indicator for low voltage			Yes
Power Rdy (Ready - minimum limit)			Yes
<b>Connections</b>			
Terminals type			Screw

**Ambient conditions**

Temperature

Operating temperature

min	°C	-30
max	°C	+71

Storage temperature

min	°C	-40
max	°C	+85

Derating

%/°C	2.5%/°C above 60°C
------	--------------------

**Housing**

Material

Metal

IEC degree of protection

IP20

Dimensions (W x H x D)

mm	150 x 124 x 118.8
----	-------------------

Weight


g	1995
---	------

**Installations**

Mounting


On 35mm DIN rail

**Dimensions**



TYPE	A	B	C
PSL1 120...	64 (2.52")	124.5 (4.90")	123.6 (4.87")
PSL1 240...	83.5 (3.29")	124.5 (4.90")	123.6 (4.87")
PSL1 300...	83.5 (3.29")	124.5 (4.90")	123.6 (4.87")
PSL1 480...	175.5 (6.91")	124.5 (4.90")	123.6 (4.87")
PSL3 120 24	74.3 (2.92")	124 (4.88")	118.8 (4.68")
PSL3 240...	89 (3.50")	124 (4.88")	118.8 (4.68")
PSL3 480...	150 (5.90")	124 (4.88")	118.8 (4.68")
PSL3 960...	275.8 (10.86")	125.9 (4.96")	120.3 (4.74")

**Wiring diagrams**



**Certifications and compliance**

Compliance

- CSA C22.2 n°14
- IEC/EN/BS 61000-6-2
- IEC/EN/BS 61000-6-3
- IEC/EN/BS 62368-1
- UL 508

Certificates

- cULus
- EAC
- RCM

**ETIM classification**

ETIM 8.0

EC002540 - DC-  
power supply