

Driver for DURASTRIP



- * Loose wires connection.
- * TUV mark.
- * IP67
- * Class I driver
- * SELV-equivalent
- * Protection in case of short circuit or overload in the secondary circuit.
- * 24Vdc.
- * 50/60Hz

Item Characteristics

	Code	ZK73200
	Lamp Voltage	100-240 V
	Base	cavi liberi / loose wires
	Lamp Current	8 A
	Input voltage	100-240V
	Lenght	238 mm
	Lenght 1	63 mm
	Lenght 2	43 mm
	Output load (W)	200 W
Performance		
	Energy Class	
Tech Info		
	Power Factor	0,9
	T (°C) Working environment Temp.	-25°C / +35°C
	Fulfilled Directives and norms	2006/95/CE * Bassa Tensione 2012/19/UE * RAEE EN 60155 * anno 1996 (+A2:2007) 2011/65/UE * RoHS
Shipping info		
	Single pack dimensions L x H x D (mm)	2730 x 1080 x 500
	Item barcode	8011905833336
	Pack	1 pz
	Master barcode	8011905778613
	Master pack dimensions L x H x D (mm)	2780 x 2650 x 3400
	,	

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.