

PRODUCT-DETAILS

E232E-8/230-MULTI1

E232E-8/230-MULTI1 Staircase Switch



Informations générales

Extension du type de produit	E232E-8/230-MULTI1
Code de produit	2CDE010013R0511
EAN	4016779654197
Description courte	E232E-8/230-MULTI1 Staircase Switch

Description longue	<p>Staircase time switches with off-delay are operated by push-buttons, which are often equipped with a glow lamp. The switch levers are designed for a glow lamp current of up to 150 mA and are therefore excellently suited for installations in multistorey buildings. The E 232E-230 staircase lighting timer with off-delay has an electromechanical timer relay with synchronous motor drive, which ensures a high level of operational safety in any installation position. The time range can be set in 15-second increments from one to seven minutes. Can be reswitched after 30s. The multifunctional units of the E 232E-230 Multi 10 and E 232E-8/230 Multi 10 product series have 10 functions that can be set on the front of the unit.</p>
--------------------	---

Technique

Fonction	Electronic switch
Reset Function	Push Button
Tension nominale (U _r)	230 V AC
Tension d'alimentation	0.85 ... 1.1 V
Additional Control Voltage	8 ... 240 V AC/DC
Maximum Control Current	26 mA

DC	
Fréquence assignée (f)	50 ... 60 Hz
Maximum Lamp Load	LED Power > 2W 600 W LED Power < 2W 55 W
Power Loss	6 V·A
Puissance Watt	Filament Lamp 3600 W Fluorescent Lamp Compensated 3600 V·A Fluorescent Lamp Shunt Capacitive 1200 V·A Fluorescent Lamp Inductive 3600 V·A Halogen Lamp 3600 W
Minimum Switching Time	0.02 second [unit of time]
Time Range	0.5 – 20 min. Stepless Long 60 min. time range available
Impulse Duration	10 second [unit of time]
Appareil	Électronique
Type de charge	2300W Inductive load, cosj = 0.6/230 VAC
Switch Type	SteadyLight
Matériau du boîtier	Heat resistant, self-extinguishing thermoplast
Options Provided	With Switch-Off Warning
Section de câble	Terminal 4 mm ² Terminal 13 mm ²
Connection Mode and Capacity	3 or 4 conductor operated automatically
Control Supply Voltage	230 AC V
Contact Material	silver-tin-oxide (AgSnO ₂)
Rated Switching Capacity	16 A 230 V AC
Switch Off Warning Type	Flickering

Environnement

Température extérieure	-25 ... 50 °C
Statut RoHS	Following EU Directive 2011/65/EU
Informations RoHS	2CDK440004K0202
REACH Declaration	9AKK107492A1907
Informations environnementales	2CDU400020D0201
SCIP	8ec0dc57-a0c8-45f0-a754-21f73a3976d7 Germany (DE)
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Produit Largeur Net	17.5 mm
Produit Hauteur Net	90 mm
Produit Longueur Net	58 mm
Poids net	0.08 kg

Commande

Emballage Niveau 1	box 10 pièce
Unités	
Emballage Niveau 1 Poids	1.005 kg

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CDK440040D0201
EAC Certificate	9AKK108466A2730
VDE Certificate	9AKK108466A2521

Installation

Instructions et manuels	2CDE100001P1
-------------------------	--------------

Downloads Préférés

Fiche produit, informations techniques	9AKK106930A8017
---	-----------------

Classifications

ETIM 8	EC000297 - Staircase lighting timer
ETIM 9	EC000297 - Staircase lighting timer
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 49 00
eClass	V11.0 : 27142307

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Control and Automation Devices → Staircase Switches

