

PRODUCT-DETAILS

6867 AGM-201-500

Outdoor Movement Detector MasterLINE

Remote control brown



Informations générales

Extension du type de produit	6867 AGM-201-500
Code de produit	2CKA006800A2557
EAN	4011395150924
Description courte	Outdoor Movement Detector MasterLINE Remote control brown

Description longue	<p>Electronic movement detector for detecting thermal motion. Remote control possible via IR remote control 6841-101 (included in scope of delivery). Remote configurable via IR service remote control 6842-101. With display for detection and operation mode. With ground and rear-field detection. With high-quality lens for optimum detection. Detection sensitivity adjustable via IR service remote control. Surveillance density: 110 sectors with 440 switching segments. With integrated dismantling protection. All functions controlled by microprocessor. Always-On (4 hours) and Presencesimulation can be activated via IR-remote control. Reading in the current brightness value as switching threshold via remote control. With automatic range stabilization. With automatic interference suppression. With automatic dazzle-proofing. With brightness-independent test mode for evaluating the detection zone. Individual adjustment of detection range via enclosed protective foil which can be cut to size. Additional possibility for switch-on via normally open push-button switch.</p> <p>Switch-off delay: 10 sec to 30 min or short-time pulse 1 sec adjustable.</p>
--------------------	--

Installation

Instructions et manuels	DEBJE-0073-1-8054
-------------------------	-------------------

Technique

Fiche produit, informations techniques	No document needed
Tension nominale (U_r)	230 V
Auxiliary Voltage AC/DC	230 V AC/DC
Type de tension	AC
Courant nominal (I_n)	16 A
Current Range	Maximum 80 A
Fréquence (f)	50...60 Hz
Fréquence assignée (f)	50 ... 60 Hz
Maximum Switching Power	3680 W
Power Loss	1 W
Plage de mesure	Diameter Detection range on floor 32 m
Nombre de sorties	1
Number of Switching Zones	1
Conception	MasterLINE
Minimum Switching Time	Switch-On 10 second [unit of time]
Type de raccordement	Cable Clamp
Type de charge	ohmic, capacitive and inductive loads
Type de montage	Surface Mounted
Sensor Type	Passive infrared
Finition de surface	Surface protection: Untreated Surface finishing: Matt
Matériau	Thermoplastic
Comprend	Remote control
Type d'encastrement	wall
Flux lumineux	0 ... 1000 lx
Model Number	Movement sensor
RAL Number	RAL 8017 - Brun chocolat
Couleur	brown
Composition chimique de la batterie	Lithium
Désignation des dimensions	CR2025
Type de batterie	Pile bouton
Poids de la batterie	2 g
Nombre de batteries	1
Application Function	Electrical Load and Light Control

Environnement

Température de l'air ambiant	Operation -25 ... +55 °C
Indice de protection	IP55
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Informations RoHS	2CKA200000E6409
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Poids net	0.56 kg
-----------	---------

Commande

ID du produit remplacé	6800-0-2557
------------------------	-------------

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E2025
--------------------------------	-----------------

Classifications

ETIM 8	EC000133 - Movement sensor complete
ETIM 9	EC000133 - Movement sensor/presence detector complete
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27144007

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006899A0231	RC suppressor 2 pole 230 V	6899	1	piece

Catégories

Produits basse tension → Wiring Accessories - StandAlone Electronics → Outdoor Movement Detector → Professional Series

