1SET315094R0000 - ACTIVE

ENTRELEC | M12 Connector

TE Internal #: 1SET315094R0000 M12 Pigtail Cable Assembly, 5 Position, 2 m, Industrial Fieldbus, DeviceNet, Code A, M12 Socket, Shielded, Single Ended, PA66+25GF

View on TE.com >

Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies



M8/M12 Application Type: Industrial Fieldbus

Industrial Protocols: DeviceNet

Number of Positions: 5

Keying Code: A

Connector Type (End A): M12 Socket

Features



Product Type Features

LED	Without
Product Type	Cable Assembly
Cable Type	PVC
Assembly Type	Overmolded
Connector Type (End A)	M12 Socket
Cable Assembly Type	M12 Pigtail
Configuration Features	
Number of Positions	5
Keying Code	A
Electrical Characteristics	
Operating Voltage	60 VDC
Body Features	
Cable Exit Angle	Straight
Environmental Protection	IP67

1SET315094R0000

M12 Pigtail Cable Assembly, 5 Position, 2 m, Industrial Fieldbus, DeviceNet, Code A, M12 Socket, Shielded, Single Ended, PA66+25GF



EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU ELV Directive 2000/53/EC	Compliant with Exemptions
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
Product Compliance	
Cable Assembly Configuration	Single Ended
Cable Assembly Length	2 m
Other	
Packaging Quantity	5
Packaging Method	Bag
Packaging Features	
Industrial Protocols	DeviceNet
ndustry Standards	
Shielded	Yes
M8/M12 Application Type	Industrial Fieldbus
Operation/Application	
Wire Size	22 – 24 AWG
Overall Outside Cable Diameter	7.1 mm
Dimensions	
Housing Material	PA66+25GF
Housing Features	
Connector Orientation (End A)	Straight
Mechanical Attachment	
Contact Current Rating	4 A
Contact Features	
Cable Jacket Color	Gray
Connector Color	Black

1SET315094R0000

M12 Pigtail Cable Assembly, 5 Position, 2 m, Industrial Fieldbus, DeviceNet, Code A, M12 Socket, Shielded, Single Ended, PA66+25GF



Halogen Content Not Low Halogen - contains Br or Cl > 900 ppm.

Solder Process Capability

Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



Also in the Series | M12 Connector



Documents

Product Drawings M12A5-FS-PVC-2.0M

English

CAD Files

C For support call+1 800 522 6752

1SET315094R0000

M12 Pigtail Cable Assembly, 5 Position, 2 m, Industrial Fieldbus, DeviceNet, Code A, M12 Socket, Shielded, Single Ended, PA66+25GF



3D PDF

3D

Customer View Model ENG_CVM_CVM_1SET315094R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SET315094R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SET315094R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages Infographic - entrelec ews-linecard English

Catalog - ENTRELEC-M8-M12-RJ45

English

Product Specifications Application Specification

English