



## Features

Use: Indoor  
 Type of installation: RECESSED INTO PLASTERBOARD  
 Emission: DIRECT  
 Optics: SPOT  
 Beam: 36°  
 Colour: GREY  
 Dimming: ON/OFF  
 Emergency: WITH ACCESSORY  
 L: Ø172mm  
 H: 90mm  
 D: 150-165mm  
 Warranty: 5 years  
 Weight: 1kg

## Tech data

Luminaire input power: 24W  
 Luminaire luminous flux: 2212lm  
 Luminous flux in emergency: 1h: 19% / 3h: 8%  
 IP: 40  
 Insulation class: II  
 Supply voltage: 220-240V 50/60Hz  
 UGR: <19  
 SELV: Si

## Source

Light source: LED  
 Source power: 22W  
 Colour temperature: 4000K  
 CRI: >90  
 LED lifespan: 50000h L80 B50

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[View more product info](#)

**EMERGENCY ACCESSORIES**

---



THE PANEL 2: EMER.INC.3H 10/54VDC

**1020A5.99**

---



THE PANEL 2: EMER.INC.1H 10/54VDC

**1020A4.99**