

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: LENS UGR<19
Colour: WHITE
Dimming: ON/OFF
Emergency: WITH ACCESSORY
L: 595mm
A: 595mm
H: 14 (30 con alim.)mm
Warranty: 5 years
Weight: 3.4kg

Tech data

Luminaire input power: 34W
Luminaire luminous flux: 4000lm
Luminous flux in emergency: 1h: 13% / 3h: 5%
IP: 40
Insulation class: II
Supply voltage: 900 mA ALIMENT.INCLUSO
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 30W
Source luminous flux: 4895lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

Conto Termico (Thermal account): Compliant with Ministerial Decree for economic development for thermal account and Ministerial Decree for Energy management (GSE) of 16 February 2016. Compliant with Safety Criteria, Electromagnetic Compatibility and Photometric Data certified by accredited laboratory.


Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[View more product info](#)




MOUNTING ACCESSORIES



SCHOOL: KIT MOLLE PER INCASSO

104107.99



THE PANEL 2: KIT INST.INC.RAS.CART.600

102028.99




SCHOOL: KIT ANTICADUTA L=3000

104119.99




KIT ALIMENTAZIONE L1200 3P BIA

108919.01



SCHOOL: KIT SOSPENSIONE H1200


104110.99



SCHOOL: KIT INST.PLAFONE 600X600


104108.01

EMERGENCY ACCESSORIES



THE PANEL 2: EMER.INC.3H 10/54VDC

1020A5.99



THE PANEL 2: EMER.INC.1H 10/54VDC

1020A4.99