



Caractéristiques de la gamme

- OptiClip - Luminaire architectural unique, à modules LED interchangeables. Solution éco-responsable permettant le remplacement des modules LED uniquement, avec système plug & play. Facilité de maintenance. Installation : encastré, en saillie ou suspendu. Dimensions : 1200x300x52mm. Caisson en Acier zingué RAL 9016. Diffuseur polycarbonate Opale avec reflecteur blanc. Equipé d'un bornier de repiquage LiLo. Flux lumineux : 3100 lm. Efficacité lumineuse : 119 lm/W. Température de couleur : 3000K . IRC 80. Angle de faisceau 85° . Luminan...

CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment		
Product design	76.0	134.0	2.3	0.0 to 0.5	Very poor circular economy performance
Manufacturing	21.5	46.5	1.9	0.5 to 1.5	Some circular economy functionality
Materials	5.0	24.0	0.8	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	18.0	43.0	1.7	2.5 to 4.0	Excellent circularity
Overall performance	120.5	247.5	1.68		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy