

PRODUCT-DETAILS

6814 U-500

Presence Detector 7 m 2000 W



Informations générales

Extension du type de produit	6814 U-500
Code de produit	2CKA006800A2518
EAN	4011395148044
Description courte	Presence Detector 7 m 2000 W

Description longue	<p>For switching lighting systems that depend on brightness and movement. Detection range (for installation height of 3 m), circular, up to 8 m in diameter. For semiautomatic and fully automatic operation. Additional activation/deactivation possibility through pushbutton input.</p> <p>Adaptation of the detection range possible using the included masking elements. With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Mounting possibility in combination with built-in installation boxes and device sockets. Ceiling installation using integrated spring bracket. Adjustment elements accessible on the front side. Low mounting height (31 mm) Surveillance density: 32 sectors with 128 switching segments. Switch-off delay: approx. 5 sec - 30 min or short-time pulse adjustable.</p>
--------------------	---

Installation

Instructions et manuels	DEBJE-ba_0173_1_7394_6814-500t
-------------------------	--------------------------------

Technique

Tension nominale (U _r)	230 V
------------------------------------	-------

Auxiliary Voltage AC/DC	230 V AC/DC
Current Range	Maximum 80 A
Fréquence (f)	50...60 Hz
Fréquence assignée (f)	50 ... 60 Hz
Maximum Switching Power	2000 W
Power Loss	1 W
Plage de mesure	7 m
Nombre de sorties	1
Minimum Switching Time	Switch-On 5 second [unit of time]
Type de charge	230 V incandescent lamps
Type de montage	Flush Mounted
Finition de surface	Surface protection: Untreated Surface finishing: Matt
Matériau	Thermoplastic
Flux lumineux	10 ... 2000 lx
RAL Number	RAL 9010 - Blanc pur
Couleur	alpine white
Application Function	Electrical Load and Light Control

Environnement

Température de l'air ambiant	Operation 0 ... +45 °C
Indice de protection	IP40
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CKA200000E6392
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Poids net	153 g
Profondeur d'encastrement (t ₂)	41 mm

Commande

ID du produit remplacé	6800-0-2518
------------------------	-------------

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E1990
--------------------------------	-----------------

Classifications

ETIM 8	EC000133 - Movement sensor complete
ETIM 9	EC000133 - Movement sensor/presence detector complete
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27144007

Catégories

Produits basse tension → Wiring Accessories - StandAlone Electronics → Presence Detector → Basic Series

