

Part number

CC 0.5 AN



Male crimp contact, CC series, 16 A, turned silver plated, wire cross section 0,5 mm², AWG 20, advanced opening

Product description		Material properties	
Product type	Crimp contact	Main material	Copper alloy
Series	CC		Compliant with exemption
Gender	Male	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Specification	Advanced opening	China RoHs - EFUP	50
Technical data		REACH SVHC substances	Yes Lead
Current	16 A	SCIP number	C0979fba-9907-458f-a94a-db781440f273
Wire cross-section	0,50 mm ²	Approvals / Standards	
AWG size	20	Certifications	CSA, EAC
Contact type	Turned silver plated	UL	ECBT2
Further technical details		General ordering information	
Weight	1,20 g	EAN13 code	8015747011174
Operating temperature range (min, max)	-40°C ... +125°C	eCl@ss 8.1	27440204
Conductors stripping length	7,5 mm	ETIM 7.0	EC000796
Packaging Information			
Sub-packaging length	50,00 mm	Sub-packaging length	50,00 mm
Sub-packaging height	44,00 mm	Sub-packaging height	44,00 mm
Sub-packaging width	50,00 mm	Sub-packaging width	50,00 mm
Sub-packaging weight	0,06 kg	Sub-packaging weight	0,06 kg
Sub-packaging volume	0,11 dm ³	Sub-packaging volume	0,11 dm ³
Sub-packaging description	Plastic box	Sub-packaging description	Plastic box
Sub-packaging quantity	50 Pcs	Sub-packaging quantity	50 Pcs
Sub-packaging EAN barcode	8015747011181	Sub-packaging EAN barcode	8015747011181

Part number

CC 0.5 AN



Catalogue drawings



CCF, CCM and CC..AN contacts

conductor section mm ²	conductor slot $\varnothing A$ (mm)	conductors stripping length (mm)
0,14-0,37	0,9	7,5
0,5	1,1	7,5
0,75	1,3	7,5
1,0	1,45	7,5
1,5	1,8	7,5
2,5	2,2	7,5
3	2,55	7,5
4	2,85	7,5

Notes

Dimensions shown in mm are not binding and may be changed without notice.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.
