

Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: BATWING
Colour: WHITE
Dimming: ON/OFF
Emergency: NO
L: 1500mm
A: 70mm
H: 40mm
Warranty: 5 years
Weight: 2.35kg

Tech data

Luminaire input power: 53W
Luminaire luminous flux: 8177lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz

Source

Light source: LED
Source power: 46W
Source luminous flux: 8480lm
Colour temperature: 4000K
CRI: >80
LED lifespan: 50000h L70 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1


Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.


[View more product info](#)

COMPLETION ACCESSORIES




LI-NEAR: MOD.TERMINALE L=210MM+TEST+SC

107204.01



LI-NEAR: TESTATE INIZIO-LINEA (COPPIA)

107205.01




LI-NEAR: MODULO CIECO 1,50M BIA+2 SCUR

107206.01




LI-NEAR: CONNETTORE 8 POLI CON MORSETTI

107226.99



LI-NEAR: GIUNTO A "L" 8 POLI


107224.01



LI-NEAR: GIUNTO A "T" 8 POLI

107225.01

MOUNTING ACCESSORIES



LI-NEAR: KIT SOSPENSIONE 3M 1 PZ.

107207.99



LI-NEAR: KIT FISSAGGIO PLAFONE (COPPIA)

107209.99