

## Features

Use: Indoor  
Type of installation: SUSPENDED  
Emission: DIRECT/INDIRECT  
Optics: OPAL  
Colour: CAFFE  
Dimming: WITH ACCESSORY  
Emergency: NO  
L: Ø962mm  
A: 40mm  
H: 50mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 6.9kg

## Tech data

Luminaire input power: 141.5W  
Luminaire luminous flux: 10144lm  
Direct luminous flux: 3947lm  
Indirect luminous flux: 6197lm  
IP: 40  
Insulation class: III  
Supply voltage: MAX 1.8A  
UGR: <19  
IK: 3  
SELV: Si

## Source

Light source: LED  
Source power: 124W  
Source luminous flux: 17004lm  
Colour temperature: 2700K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

# HALOS B

107119.20

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

## MOUNTING ACCESSORIES

---



HALOS: ROSONE ALIM. REMOTA BIA

**105157.01**

---



HALOS: ROSONE ALIM. REMOTA CAFFE

**105157.20**

---



HALOS: ROSONE DOPPIA ALIM. REMOTA BIA

**105158.01**

---




HALOS: ROSONE DOPPIA ALIM. REMOTA CAFFE

**105158.20**

## ELECTRICAL ACCESSORIES

---



HALOS-B: COPPIA ALIM. ON/OFF REM.

**107125.99**

---



HALOS-B: ROSONE ALIM. ON/OFF BI

**107127.01**



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.

# HALOS B

107119.20

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



HALOS-B: ROSONE ALIM. ON/OFF CAFFE

**107127.20**



HALOS-B: ROSONE-N ALIM. ON/OFF BIA


**107129.01**



HALOS-B: ROSONE-N ALIM. ON/OFF CAFFE

**107129.20**

## DIMMABLE ACCESSORIES



HALOS-B: COPPIA ALIM. DALI/PUSH REM.

**107126.99**



HALOS-B: ROSONE ALIM. DALI/PUSH BI

**107128.01**



HALOS-B: ROSONE ALIM. DALI/PUSH CAFFE

**107128.20**



HALOS-B: ROSONE-N ALIM. D/PUSH BI

**107130.01**



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.

# HALOS B

107119.20

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



HALOS-B: ROSONE-N ALIM. D/PUSH CAFFE

**107130.20**



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.