




Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: SPOT
Beam: 36°
Colour: BLACK
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
A: Ø65mm
H: 105mm
D: 60mm
Warranty: 5 years
Weight: 0.315kg

Tech data

Luminaire luminous flux: 560lm
Luminous flux in emergency: 1h: 44% / 3h: 18%
IP: 20
Insulation class: III
Supply voltage: DC 500 mA
SELV: No



Source

Light source: LED
Source power: 10W
Colour temperature: 2700K
CRI: >90
LED lifespan: 30000h

Compliance


CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.


[View more product info](#)

ELECTRICAL ACCESSORIES



ALIM. LED MAX 18W 500MA


101325.99



ALIM. LED 15W/500MA


101307.99

DIMMABLE ACCESSORIES




ALIM. MAX.20W/500MA DALI/PUSH/0-10/1-10

101904.99



ALIM. LED MAX 10W 500MA DALI PUSH


101316.99



ALIM. LED 25W 500MA/2-50V DALI/PUSH

101334.99

EMERGENCY ACCESSORIES



KIT EMERGENZA 3H 10V-54V


18005.99

KONE

103630.02

novalux

ITALIAN LIGHTING DESIGN SINCE 1948



KIT EMERGENZA 1H 10V-54V

18004.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.