
ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR LEVER Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 - 0 < 2



Product designation				Selector switch actuators long lever - 3 position
Product type designation General characteristics				LPFS23
				Dlook
Colour				Black
Type of positions				Selector switch
Material				Aluminium and zinc alloy
IEC degree of protect	tion			IP66, IP67 and IP69K
Mechanical features				
Mechanical life			cycles	1000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120M
UL technical data				
UL degree of protection				Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			
	-	min	°C	-40
		max	°C	+85
Dimensions				

Dimensions



Certifications and compliance

\sim			
Com	nlia	anr	םי
COIII	viic	אווג	,0

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1

UL508

Certificates

cULus

ETIM classification





SELECTOR SWITCH ACTUATOR LEVER Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 - 0 < 2

ETIM 8.0

EC002611 -Control switch