

PRODUCT-DETAILS

SD203/32

SD203/32 Switch Disconnecter



Informations générales

Extension du type de produit	SD203/32
Code de produit	2CDD283101R0032
EAN	4016779904209
Description courte	SD203/32 Switch Disconnecter
Description longue	SD203/32 - Switch Disconnecter - 3P, 32A

Technique

Normes et standards	IEC/EN 60947-3
Tension nominale (U_r)	440 V 12 V Minimum
Tension	440 V AC
Operational Voltage	Maximum 462 V AC Minimum 12 V AC
Tension assignée de tenue aux chocs (U_{imp})	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
Type de tension	AC
Courant nominal (I_n)	32 A
Rated Conditional Short-Circuit Current (I_{nc})	25 kA
Fréquence assignée (f)	50 / 60 Hz

Power Loss		at Rated Operating Conditions per Pole 1.81 W
Contact Position Indication		ON / OFF
Electrical Endurance		10000 AC cycle
Mechanical Endurance		20000 cycle
Number of Contacts CO		0
Number of Contacts NC		0
Number of Contacts NO		3
Nombre de pôles		3
Catégorie de Surtension		III
Couple de serrage		2.8 N·m
Utilization Category	Switching of motor loads or other highly inductive loads - frequent actuation (AC -23A)	
Actuator Type		Toggle
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal	
Switch Type		Off
Actuator Marking		I / O
Actuator Material	Insulation Group II, Red, Sealable	
Qualité du matériau	Insulation Group I, RAL 7035	
Type d'encastrement		any
Recommended Screw Driver		Pozidriv 2
Accessories Available		Oui
Cover Color		Grey
Connecting Capacity	Busbar 10 / 10 mm ² Flexible 0.75 ... 16 mm ² Rigid 0.75 ... 25 mm ² Stranded 0.75 ... 25 mm ²	
Type de borne	Screw Terminals	

Environnement

Température de l'air ambiant	Operation -25 ... +55 °C Storage -40 ... +70 °C	
Indice de protection	IP20 Enclosure with Cover IP40	
Degré de pollution	3	
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %	
Resistance to Vibrations acc. to IEC 60068-2-6	5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In	
Résistance aux chocs selon CEI 60068-2-27	25g 2 shocks 13 ms	
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
Informations RoHS	2CDK440034D2703	
REACH Declaration	9AKK107492A1906	
Informations environnementales	2CDK400618D0201	
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363	

Dimensions

Width in Number of Modular Spacings	3
-------------------------------------	---

Produit Largeur Net	52.5 mm
Produit Hauteur Net	88 mm
Produit Longueur Net	69 mm
Poids net	0.255 kg
Profondeur d'encastrement (t ₂)	69 mm

Commande

Emballage Niveau 1 Unités	1 pièce
Emballage Niveau 1 Poids	0.27 kg
E-Number (Finland)	3601639

Certificats et Déclarations (Numéro de document)

Agence de certification	IEC EN
Déclaration de Conformité - CE	2CDC440034D2703

Installation

Instructions et manuels	2CDC441015D0201
-------------------------	-----------------

Downloads Préférés

Fiche produit, informations techniques	2CDC441015D0201
--	-----------------

Classifications

ETIM 8	EC001545 - Main switch for distribution board
ETIM 9	EC001545 - Main switch for distribution board
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 90 95
eClass	V11.0 : 27142301
Code de classification d'objet	Q

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CDS200912R0001	S2C-H6R Auxiliary Contact	S2C-H6R	1	piece
2CDS200970R0001	S2C-H01 Auxiliary Contact	S2C-H01	1	piece
2CDS200970R0002	S2C-H10 Auxiliary Contact	S2C-H10	1	piece
2CDS200936R0001	S2C-H11L Auxiliary Contact	S2C-H11L	1	piece
2CDS200936R0002	S2C-H20L Auxiliary Contact	S2C-H20L	1	piece
2CDS200936R0003	S2C-H02L Auxiliary Contact	S2C-H02L	1	piece
2CDS200946R0001	S2C-H6-11R Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0002	S2C-H6-20R Auxiliary Contact	S2C-H6-20R	1	piece
2CDS200946R0003	S2C-H6-02R Auxiliary Contact	S2C-H6-02R	1	piece
2CDS200909R0001	S2C-A1 Shunt Trip	S2C-A1	1	piece
2CDS200909R0002	S2C-A2 Shunt Trip	S2C-A2	1	piece
2CSS200911R0001	S2C-UA 12 DC Undervoltage Release	S2C-UA 12 DC	1	piece
2CSS200911R0002	S2C-UA 24 AC Undervoltage Release	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC Undervoltage Release	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC Undervoltage Release	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC Undervoltage Release	S2C-UA 230 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC Undervoltage Release	S2C-UA 400 AC	1	piece
2CSS200911R0007	S2C-UA 24 DC Undervoltage Release	S2C-UA 24 DC	1	piece
2CSS200911R0008	S2C-UA 48 DC Undervoltage Release	S2C-UA 48 DC	1	piece
2CSS200911R0009	S2C-UA 110 DC Undervoltage Release	S2C-UA 110 DC	1	piece
2CSS200911R0010	S2C-UA 230 DC Undervoltage Release	S2C-UA 230 DC	1	piece
2CSS201997R0013	S2C-CM1 Motor operating device	S2C-CM1	1	piece
2CSS203997R0013	S2C-CM2/3 Motor operating device	S2C-CM2/3	1	piece
2CSS204997R0013	S2C-CM4 Motor operating device	S2C-CM4	1	piece
GHS2001901R0003	S2C-DH Mechanical Accessories	S2C-DH	1	piece
2CSS200998R0001	S2C-BP Mechanical tripping device	S2C-BP	1	piece
2CSS200999R0001	S2C-EST Plug-in base	S2C-EST	1	piece
2CDS200918R0001	S2C-NT Hand Operated Neutral	S2C-NT	1	piece
2CCA880100R0001	CMS-100PS Sensor	CMS-100PS	1	piece
2CCA880101R0001	CMS-101PS Sensor	CMS-101PS	1	piece
2CCA880102R0001	CMS-102PS Sensor	CMS-102PS	1	piece

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Command and Signalling Devices → Switch Disconnectors
 Produits et Systèmes Moyenne Tension → Service → Pièces détachées → Parts → All Spare Parts (Relays-SWG-CB)

