

Speed controller, 2.4 A, 0.75 kW, Sensor input 4, AS-Interface®, S-7.4 for 31 modules, HAN Q5, with manual override switch



Powering Business Worldwide™

**Part no. RASP5-2400A31-512R000S1
198548**

Product name	Eaton Moeller® series Rapid Link Speed controller
Part no.	RASP5-2400A31-512R000S1
EAN	4015081964239
Product Length/Depth	157 millimetre
Product height	270 millimetre
Product width	220 millimetre
Product weight	3.58 kilogram
Certifications	UL 61800-5-1 CE RoHS UL approval IEC/EN 61800-5-1
Product Tradename	Rapid Link
Product Type	Speed controller
Product Sub Type	None
Catalog Notes	3 fixed speeds and 1 potentiometer speed can be switched over from U/f to (vector) speed control Connection of supply voltage via adapter cable on round or flexible busbar junction Diagnostics and reset on device and via AS-Interface integrated PTC thermistor monitoring and Thermoclick with safe isolation optional: 4 sensor inputs with M12-Y adapter for switchover to creep speed optional: Faster stop if external 24 V fails Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation with AUTO - OFF/RESET - HAND key switches with selector switch REV - OFF - FWD
Features	Parameterization: drivesConnect Parameterization: Fieldbus Parameterization: Keypad Diagnostics and reset on device and via AS-Interface Parameterization: drivesConnect mobile (App)
Fitted with:	Key switch position AUTO Key switch position OFF/RESET Key switch position HAND Internal DC link Manual override switch PC connection Thermo-click with safe isolation Selector switch (Positions: REV - OFF - FWD) PTC thermistor monitoring Control unit Two sensor inputs through M12 sockets (max. 150 mA) for quick stop and interlocked manual operation IGBT inverter
Functions	3 fixed speeds 1 potentiometer speed
Degree of protection	IP65 NEMA 12
Electromagnetic compatibility	1st and 2nd environments (according to EN 61800-3)
Overvoltage category	III
Product category	Speed controller
Protocol	AS-Interface profile cable: S-7.4 for 31 modules ASI
Radio interference class	C1: for conducted emissions only C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
Rated impulse withstand voltage (Uimp)	2000 V
System configuration type	Phase-earthed AC supply systems are not permitted. AC voltage Center-point earthed star network (TN-S network)

Mounting position		Vertical
Shock resistance		15 g, Mechanical, According to IEC/EN 60068-2-27, 11 ms, Half-sinusoidal shock 11 ms, 1000 shocks per shaft
Vibration		Resistance: 57 Hz, Amplitude transition frequency on acceleration Resistance: 6 Hz, Amplitude 0.15 mm Resistance: 10 - 150 Hz, Oscillation frequency Resistance: According to IEC/EN 60068-2-6
Altitude		Above 1000 m with 1 % performance reduction per 100 m Max. 2000 m
Ambient operating temperature - min		-10 °C
Ambient operating temperature - max		40 °C
Ambient storage temperature - min		-40 °C
Ambient storage temperature - max		70 °C
Climatic proofing		In accordance with IEC/EN 50178 < 95 %, no condensation
Current limitation		Adjustable, motor, main circuit 0.2 - 2.4 A, motor, main circuit
Delay time		< 10 ms, On-delay < 10 ms, Off-delay
Efficiency		97 % (η)
Heat dissipation at current/speed		27.5 W at 50% current and 90% speed 31.8 W at 100% current and 90% speed 33.5 W at 25% current and 50% speed 34.6 W at 50% current and 50% speed 35.1 W at 25% current and 0% speed 36.6 W at 100% current and 50% speed 36.8 W at 50% current and 0% speed 40.7 W at 100% current and 0% speed
Input current ILN at 150% overload		2.5 A
Leakage current at ground IPE - max		3.5 mA
Mains current distortion		120 %
Mains switch-on frequency		Maximum of one time every 60 seconds
Mains voltage - max		480 V
Mains voltage - min		380 V
Mains voltage tolerance		380 - 480 V (-10 %/+10 %, at 50/60 Hz)
Operating mode		Synchronous reluctance motors U/f control Sensorless vector control (SLV) PM and LSPM motors BLDC motors
Output frequency - max		500 Hz
Output frequency - min		0 Hz
Overload current		At 40 °C For 60 s every 600 s
Overload current IL at 150% overload		3.6 A
Rated frequency - max		66 Hz
Rated frequency - min		45 Hz
Rated operational current (I _e)		2.4 A at 150% overload (at an operating frequency of 8 kHz and an ambient air temperature of +40 °C)
Rated operational power at 380/400 V, 50 Hz, 3-phase		0.75 kW
Rated operational voltage		400 V AC, 3-phase 480 V AC, 3-phase
Resolution		0.1 Hz (Frequency resolution, setpoint value)
Starting current - max		200 %, IH, max. starting current (High Overload), For 2 seconds every 20 seconds, Power section
Supply frequency		50/60 Hz
Switching frequency		8 kHz, 4 - 32 kHz adjustable, fPWM, Power section, Main circuit
Assigned motor power at 460/480 V, 60 Hz, 3-phase		1 HP
Braking current		≤ 0.6 A (max. 6 A for 120 ms), Actuator for external motor brake
Braking torque		Adjustable to 100 % (I/I _e), DC - Main circuit

Rated conditional short-circuit current (Iq)		10 kA
Short-circuit protection (external output circuits)		Type 1 coordination via the power bus' feeder unit, Main circuit
Rated control voltage (Uc)		24 V DC (-15 %/+20 %, external via AS-Interface® plug)
Communication interface		AS-Interface
Connection		Plug type: HAN Q5
Interfaces		Specification: S-7.4 (AS-Interface®) Max. total power consumption from AS-Interface® power supply unit (30 V): 190 mA Number of slave addresses: 31 (AS-Interface®)
Cable length		C3 ≤ 25 m, maximum motor cable length C2 ≤ 5 m, maximum motor cable length C1 ≤ 1 m, maximum motor cable length
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Frequency converter =< 1 kV (EC001857)			
Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency converter = < 1 kV (ec@ss10.0.1-27-02-31-01 [AKE177014])			
Mains voltage	V		380 - 480
Mains frequency			50/60 Hz
Number of phases input			3
Number of phases output			3
Max. output frequency	Hz		500
Max. output voltage	V		500
Nominal output current I2N	A		2.4
Max. output at quadratic load at rated output voltage	kW		0.75
Max. output at linear load at rated output voltage	kW		0.75
Relative symmetric net frequency tolerance	%		10
Relative symmetric net voltage tolerance	%		10
Number of analogue outputs			0
Number of analogue inputs			0

Number of digital outputs			0
Number of digital inputs			4
With control element			Yes
Application in industrial area permitted			Yes
Application in domestic- and commercial area permitted			Yes
Supporting protocol for TCP/IP			No
Supporting protocol for PROFIBUS			No
Supporting protocol for CAN			No
Supporting protocol for INTERBUS			No
Supporting protocol for ASI			Yes
Supporting protocol for KNX			No
Supporting protocol for Modbus			No
Supporting protocol for Data-Highway			No
Supporting protocol for DeviceNet			No
Supporting protocol for SUCONET			No
Supporting protocol for LON			No
Supporting protocol for PROFINET IO			No
Supporting protocol for PROFINET CBA			No
Supporting protocol for SERCOS			No
Supporting protocol for Foundation Fieldbus			No
Supporting protocol for EtherNet/IP			No
Supporting protocol for AS-Interface Safety at Work			No
Supporting protocol for DeviceNet Safety			No
Supporting protocol for INTERBUS-Safety			No
Supporting protocol for PROFIsafe			No
Supporting protocol for SafetyBUS p			No
Supporting protocol for BACnet			No
Supporting protocol for other bus systems			No
Number of HW-interfaces industrial Ethernet			0
Number of interfaces PROFINET			0
Number of HW-interfaces RS-232			0
Number of HW-interfaces RS-422			0
Number of HW-interfaces RS-485			1
Number of HW-interfaces serial TTY			0
Number of HW-interfaces USB			0
Number of HW-interfaces parallel			0
Number of HW-interfaces other			1
With optical interface			No
With PC connection			Yes
Integrated breaking resistance			No
4-quadrant operation possible			No
Type of converter			U converter
Degree of protection (IP)			IP65
Degree of protection (NEMA)			12
Height		mm	270
Width		mm	220
Depth		mm	157