


PRODUCT-DETAILS

DDA802A-100/0.03 APR

DDA802A-100/0.03 APR Residual Current Device Block



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | DDA802A-100/0.03 APR |
| Code de produit | 2CSB802401R1000 |
| EAN | 8012542544630 |
| Description courte | DDA802A-100/0.03 APR Residual Current Device Block |
| Description longue | The RCD Block DDA800 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product provides the best compromise between safety and continuity in the service, thanks to the resistance to unwanted trippings. It is suitable for assembly with MCBs S800 series up to 100A. |

Technique

| | |
|--|----------------------------------|
| Normes et standards | IEC EN 60947-2 Ann. B |
| Type of Residual Current | A type |
| Adapté pour | S800S S800N S800C S800B |
| Tension nominale (U_n) | 230 V AC 240 V AC 400 V AC |
| Tension | 400/690 V |
| Tension assignée d'isolement (U_i) | 690 V |

| | |
|---|---|
| Tension assignée de tenue aux chocs (U_{imp}) | 6 kV |
| Courant nominal (I_n) | 100 A |
| Rated Residual Current | 30 mA |
| Maximum Surge Current | 3 kA |
| Leakage Current Type | A |
| Fréquence assignée (f) | 50 ... 60 Hz |
| Power Loss | 7 W |
| Nombre de pôles | 2 |
| Operating Characteristic | Instantaneous (APR High Immunity) |
| Options Provided | - |
| Connecting Capacity | Rigid 6 ... 50 mm ² Flexible 6 ... 70 mm ² |

Environnement

| | |
|---|--|
| Température extérieure | -25...60 °C |
| Température de l'air ambiant | Operation -25...60 °C |
| Indice de protection | IP2X |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 9AKK106713A5616 |
| REACH Declaration | 9AKK108467A9482 |
| Informations environnementales | refer to RoHS information |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Technique UL/CSA

| | |
|-------------------------------------|-----------------|
| Short-Circuit Current Rating (SCCR) | 0.03 ... 0.03 A |
|-------------------------------------|-----------------|

Dimensions

| | |
|-------------------------------------|----------|
| Width in Number of Modular Spacings | 4.5 |
| Produit Largeur Net | 81 mm |
| Produit Hauteur Net | 108.2 mm |
| Produit Longueur Net | 82.3 mm |
| Poids net | 0.300 kg |

Commande

| | |
|---------------------------|-------------|
| Emballage Niveau 1 Unités | box 1 pièce |
| Emballage Niveau 1 Poids | 0.4 kg |

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Déclaration de Conformité - CE | 9AKK106713A5616 |
|--------------------------------|-----------------|

Installation

Instructions et manuels

2CSB427001D0003

Downloads Préférés

Fiche produit, informations techniques

2CSC400002D0209

Classifications

| | |
|--------------------------------|--|
| ETIM 8 | EC002297 - Residual current circuit breaker (RCCB) module |
| ETIM 9 | EC002297 - Residual current circuit breaker (RCCB) module |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business |
| CN8 | 85363030 |
| eClass | V11.0 : 27142210 |
| Code de classification d'objet | F |

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → High Performance Circuit Breakers HPCBs → Accessoires pour Disjoncteurs ≤125A

