


PUSHBUTTON ACTUATOR, SPRING RETURN, WITH SYMBOL Ø22MM PLATINUM SERIES METAL, FLUSH, 0/BLACK



Product designation				Pushbutton actuators, spring return, with symbol
Product type designation				LPSB11
General characteristics	S			
Colour				Black
Type of positions				Flush pushbutton
Material			Aluminium and zinc alloy	
IEC degree of protection				IP66, IP67 and IP69K
Mechanical features				
Operating force			kg-lb	<0.5Kg / 1.1lb
Mechanical life			cycles	5000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120M
UL technical data				
UL degree of protection				Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			
		min	°C	-40
		max	°C	+85
Dimensions				



Certifications and compliance

_				
Com		l: _		
1.717	ורזו	112	rvc	. С

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 UL508

Certificates

LPSB1102

cULus

ETIM classification



LPSB1102

PUSHBUTTON ACTUATOR, SPRING RETURN, WITH SYMBOL Ø22MM PLATINUM SERIES METAL, FLUSH, 0/BLACK

ETIM 8.0

EC000221 -Front element for push button