

Resisto 1500 HE IP66 25W 4000lm 840 DALI 0010273



Caractéristiques de la gamme

• Resisto 1500 HE IP66 25W 4000lm 840 DALI - Solution étanche Led en polycarbonate. Étriers coulissants en inox 301 et platine LED fixée à la vasque. Pré-perçage aux extrémités pour 1 ou 2 presse-étoupes et pré-perçage pour alimentation par le milieu. Température de couleur 4000K, IRC80. Flux lumineux sortant 4000lm. Puissance consommée 25W. Efficacité lumineuse : 160lm/W. Version haute efficacité (HE). Facteur de puissance : 0,95. Taux de distorsion harmonique : 20%. Durée de vie (L80) : 69.000h. Risque photobiologique RG1, IP66, IK08....

CIBSE TM66

Result			
Category	Points Scored	Maximum possible points	Assessment
Product design	63.0	134.0	1.9
Manufacturing	19.2	46.5	1.7
Materials	5.0	24.0	0.8
Ecosystem	17.0	43.0	1.6
Overall performance	104.2	247.5	1.50

How to analyse the score	
0.0 to 0.5	Very poor circular economy performance
0.5 to 1.5	Some circular economy functionality
1.5 to 2.5	Definite/substantial progress to circularity
2.5 to 4.0	Excellent circularity

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy