

PRODUCT-DETAILS

DP7-S-625

DP7-S-625 ABB-free@homeTouch 7"



Informations générales

| | |
|------------------------------|---------------------------------|
| Extension du type de produit | DP7-S-625 |
| Code de produit | 2CKA008300A0357 |
| EAN | 4011395182383 |
| Description courte | DP7-S-625 ABB-free@homeTouch 7" |

| | |
|--------------------|--|
| Description longue | <p>For ABB-free@home® and ABB-Welcome. For the central control of up to 16 configurable ABB-free@home® functions of type: switching, dimming, blind, RTC, scene, Philips HUE. Display of the video image of the outdoor station. During the conversation a picture of the visitor can be taken and stored in the picture memory. For door calls during absence three pictures of the visitor are automatically stored in the picture memory. With hands-free function, volume is adjustable. Easy operation keys for door openers, mute function and light. Different bell sounds are adjustable for door and floor ringing five polyphone bell sounds are available. Volume of bell sounds is adjustable. SD card slot for extension of the picture memory. Suitable as room temperature controller extension unit (up to 8). For surface mounting. The bus can be connected via enclosed terminal block. Display size: 17.8 cm (7") Display resolution: 800 x 480 Consumer units: 11</p> |
|--------------------|--|

Installation

| | |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

Technique

| | |
|--|-----------------|
| Fiche produit, informations techniques | 2CKA001173B8598 |
|--|-----------------|

| | |
|------------------------|--|
| Compatible Bus Systems | free@home |
| Product Range | free@home |
| Type de montage | Surface Mounted |
| Finition de surface | Surface protection: Untreated Surface finishing: Glossy |
| Matériau | Thermoplastic |
| RAL Number | RAL 9005 - Noir foncé |
| Couleur | black |
| Poids de la batterie | 0 g |
| Nombre de batteries | 0 |
| Taille d'écran | 7 in |

Environnement

| | |
|---|--|
| Température de l'air ambiant | Operation -5 ... +40 °C |
| Indice de protection | IP30 |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 2CKA200000E6926 |
| REACH Declaration | 2CKA309999E9999 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|---|-------|
| Poids net | 600 g |
| Profondeur d'encastrement (t ₂) | 0 mm |

Commande

| | |
|------------------------|-------------|
| ID du produit remplacé | 8300-0-0357 |
|------------------------|-------------|

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Déclaration de Conformité - CE | 2CKA100000E2417 |
|--------------------------------|-----------------|

Classifications

| | |
|----------------|--|
| ETIM 8 | EC000677 - Display for bus system |
| ETIM 9 | EC000677 - Display for bus system |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 8517 79 00 |

Catégories

Produits basse tension → Home and Building Automation → free@home → Visualisation, Display and Signalling → Touch Panels

Produits basse tension → Home and Building Automation → Portiers vidéo → Welcome → Indoor Stations

