

Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Optics: MICRO OPTICS
Colour: BLACK
Dimming: ON/OFF
Emergency: NO
L: 1428mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years
Weight: 4.2kg

Tech data

Luminaire input power: 40.5W
Luminaire luminous flux: 4020lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 36W
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance


CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.


[View more product info](#)

COMPLETION ACCESSORIES




HERO: MOD.CIECO 250 NE

108676.02




HERO: MOD.CIECO ANG.SX 150 NE

108677.02




HERO: MOD.CIECO ANG.DX 150 NE

108678.02




HERO: MOD.CIECO 1120 NE

108679.02




HERO: MOD.CIECO 1400 NE

108680.02



HERO: MOD.CIECO 1680 NE

108681.02



HERO: COPPIA TESTATE NE

108684.02

MOUNTING ACCESSORIES



ALL-TRACK: COPPIA ADATT. 3P NER

106722.02



HERO: SOSPL3000 1PZ. TESTA/CODA

108685.99



HERO: SOSPL3000 1PZ. UNIONE

108686.99



HERO: STAFFA PARETE "L" NE

108687.02



HERO: KIT INCASSO LED (1X)

108688.99




HERO: SPESS. CARTONG. 10MM 2PZ.

108689.99



KIT ALIMENTAZIONE L1200 3P BIA

108919.01




KIT ALIMENTAZIONE L1200 3P NE

108919.02



KIT ALIMENTAZIONE L3000 3P BIA

108920.01



KIT ALIMENTAZIONE L3000 3P NE

108920.02