

Certificates

ETIM 8.0

ETIM classification

cULus



Illuminated button

Product designation				actuators, spring return - Extended
Product type designati				LPSBL20
General characteristics	S			
Colour				Green
Type of positions				Extended pushbutton
Material				Aluminium and zinc alloy
IEC degree of protect	ion			IP66, IP67 and IP69K
Mechanical features				
Mechanical life - spring return actuators			cycles	5000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120M
UL technical data				
UL degree of protection	on			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature		° <b>0</b>	05
		min	℃ ℃	-25 +70
	Storage temperature	max	U	+70
	Storage temperature	min	°C	-40
		max	°C	+85
Dimensions			-	
	- 029.5 (1.16")			
Certifications and com	pliance			
Compliance				
	CSA C22.2 n° 14			
	IEC/EN/BS 60947-1			
	IEC/EN/BS 60947-5-1			
	UL508			

I PSBI 203	The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and
	functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

EC000221 -

Front element for push button