
PUSHBUTTON ACTUATOR, SPRING RETURN Ø22MM PLATINUM SERIES METAL, FLUSH,



Product designation				Pushbutton actuator, spring return
Product type designa	tion			LPSB10
General characteristic	os estados esta			
Colour				White
Type of positions				Flush pushbutton
Material				Aluminium and zinc alloy
IEC degree of protec	tion			IP66, IP67 and IP69K
Mechanical features				
Operating force			kg-lb	<0.5Kg / 1.1lb
Mechanical life - sprin	g return actuators		cycles	5000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120M
UL technical data				
UL degree of protecti	on			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			
		min	°C	-40
		max	°C	+85
Dimensions				

Dimensions



Certifications and compliance

Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 UL508

Certificates

cULus

ETIM classification

ETIM 8.0

EC000221 -Front element for push button





PUSHBUTTON ACTUATOR, SPRING RETURN Ø22MM PLATINUM SERIES METAL, FLUSH, WHITE