

Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: LENS UGR<19
Beam: 60°
Colour: WHITE
Dimming: ON/OFF
Emergency: NO
L: 1693mm
A: 60mm
H: 80mm
Made in: ITALY
Warranty: 5 years
Weight: 5.3kg

Tech data

Luminaire input power: 39W
Luminaire luminous flux: 4949lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
UGR: <19
SELV: No

Source

Light source: LED
Source power: 36W
Source luminous flux: 5187lm
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B10

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[View more product info](#)




MOUNTING ACCESSORIES




HERO: SOSPL3000 1PZ. TESTA/CODA

108685.99



KIT ALIMENTAZIONE L3000 5P BIA

108922.01



KIT ALIMENTAZIONE L3000 3P BIA

108920.01
