

PRODUCT-DETAILS

NF40E-11

NF40E-11 24-60V50/60HZ 20-60VDC Contactor Relay



Informations générales

Extension du type de produit	NF40E-11
Code de produit	1SBH137001R1140
EAN	3471523100015
Description courte	NF40E-11 24-60V50/60HZ 20-60VDC Contactor Relay

Description longue	<p>NF contactor relays are used for switching auxiliary and control circuits. NF contactor relays include an electronic coil interface accepting a wide control voltage U_c min. ... U_c max. Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. NF contactor relays can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. NF contactor relays have built-in surge protection and do not require additional surge suppressors. - Poles: 4-pole contactor relays - Control Circuit: AC or DC operated - Accessories: a wide range of Accessories is available. Note: NF..E-11 not suitable for a direct control by PLC-output. NF..E-11 type available in some countries: please consult your ABB representative.</p>
--------------------	---

Commande

Quantité minimum	1 pièce
Code douanier	85364900

Downloads Préférés

Instructions et manuels	1SBC101027M6801
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Produit Largeur Net	45 mm
Produit Longueur Net	77 mm
Produit Hauteur Net	86 mm
Poids net	0.27 kg

Technique

Number of Auxiliary Contacts NO	4
Number of Auxiliary Contacts NC	0
Normes et standards	IEC/EN 60947-1, IEC/EN 60947-5-1, UL 508, CSA C22.2 No. 14-13
Tension	Circuit auxiliaire 690 V
Fréquence assignée (f)	Circuit auxiliaire 50 / 60 Hz Circuit de commande 50 / 60 Hz
Courant thermique conventionnel à l'air libre (I_{th})	acc. to IEC 60947-5-1, $\Theta = 40\text{ °C}$ 16 A
Courant assignée d'emploi AC-15 (I_g)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Courant assigné de courte durée admissible (I_{cw})	for 0.1 s 140 A for 1 s 100 A
Maximum Electrical Switching Frequency	(AC-15) 1200 cycles per hour (DC-13) 900 cycles per hour
Courant assignée d'emploi DC-13 (I_g)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Tension assignée d'isolement (U_i)	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Tension assignée de tenue aux chocs (U_{imp})	6 kV
Maximum Mechanical Switching Frequency	6000 cycles per hour
Rated Control Circuit Voltage (U_c)	50 Hz 24 ... 60 V 60 Hz 24 ... 60 V DC Operation 20 ... 60 V
Durée de fonctionnement nominale	Entre la mise hors tension de la bobine et la fermeture du contact NC (normally closed) 13 ... 98 ms Entre la mise hors tension de la bobine et l'ouverture du contact NO (normally

	open) 11 ... 95 ms
	Entre la mise sous tension de la bobine et l'ouverture du contact NC 38 ... 90 ms
	Entre la mise sous tension de la bobine et la fermeture du contact NO 40 ... 95 ms
Montage sur rail DIN	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied)	2 x M4 screws placed diagonally
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Wire Stripping Length	Auxiliary Circuit 10 mm Control Circuit 10 mm
Indice de protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20
Type de borne	Screw Terminals

Technique UL/CSA

Connecting Capacity Auxiliary Circuit UL/CSA	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 11 in-lb Control Circuit 11 in-lb

Environnement

Température de l'air ambiant	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air -40 ... 70 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Altitude de fonctionnement maximale autorisée	Without Derating 3000 m
REACH Declaration	2CMT2021-006202
Résistance aux chocs selon CEI 60068-2-27	Closed, Shock Direction: B1 25 g Open, Shock Direction: B1 5 g Shock Direction: A 30 g Shock Direction: B2 15 g Shock Direction: C1 25 g Shock Direction: C2 25 g
Resistance to Vibrations acc. to IEC 60068-2-6	5 ... 300 Hz 4 g closed position / 2 g open position
Informations RoHS	2CMT2021-006277
Statut RoHS	Following EU Directive 2011/65/EU

Certificats et Déclarations (Numéro de document)

Certificat ABS	ABS_20-2060694-PDA
----------------	--------------------

Certificat BV	BV_2634H24899C0
CB Certificate	CB_SE-93051M2
CCC Certificate	2020980303000185
CQC Certificate	CQC2019010303267993
Declaration of Conformity - CCC	CQC2011010303465426
Déclaration de Conformité - CE	1SBD250005U1000
Declaration of Conformity - UKCA	1SBD250036U1000
Certificat DNV	DNV_TAE00001BV-5
EAC Certificate	EAC_RU C-FR ME77 B03544
Certificat GOST	GOST_POCCFR.ME77.B06804.pdf
KC Certificate	KC-HW02016-21031A
Certificat LR	LRS_LR2003684TA
Certificat RINA	RINA_ELE240318XG
Certificat RMRS	RMRS_1802702280
Certificat UL	UL_20180227_E252354_2_1
UL Listing Card	UL_E252354

Emballage

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	87 mm
Emballage Niveau 1 Longueur	79 mm
Emballage Niveau 1 Hauteur	47 mm
Emballage Niveau 1 Poids	0.27 kg
Emballage Niveau 1 EAN	3471523100015
Emballage Niveau 2 Unités	box 27 pièce
Emballage Niveau 2 Largeur	250 mm
Emballage Niveau 2 Longueur	300 mm
Emballage Niveau 2 Hauteur	315 mm
Emballage Niveau 2 Poids	14.58 kg
Emballage Niveau 3 Unités	1296 pièce

Classifications

Code de classification d'objet	K
ETIM 4	EC000196 - Contactor relay
ETIM 5	EC000196 - Contactor relay

ETIM 6	EC000196 - contacteur auxiliaire, relais
ETIM 7	EC000196 - Contactor relay
ETIM 8	EC000196 - Contactor relay
eClass	V11.0 : 27371001
UNSPSC	39121529
Code de catégorie granulaire IDEA (IGCC)	4763 >> Power contactor, DC switching
E-Number (Finland)	3705815
E-Number (Sweden)	3211472

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Contacteurs → Contacteurs monoblocs → NF
Contactor Relays

