

PRODUCT-DETAILS

Q855B410

Q855B410 Cabinet, Rows: 6, 1049 mm x 396 mm x 250 mm, Grounded (Class I), IP55



Informations générales

| | |
|------------------------------|---|
| Extension du type de produit | Q855B410 |
| Code de produit | 1SZE550800B0030 |
| EAN | 3800161600739 |
| Description courte | Q855B410 Cabinet, Rows: 6, 1049 mm x 396 mm x 250 mm, Grounded (Class I), IP55 |
| Description longue | Wallcabinet, Type System pro E energy M, Basic structure, Mountingtype: Wallhanging, for indoor installation, Flatpack, Protection form I (Earthed), Protectclass IP55 (with door) IP30, without door, Acc.Norm: IEC 61439-1, IEC 61439-2, IEC 61439-3; IEC62208, IK08 for housing, IK07 for glass-door and knock-out, powdercoated RAL 7035, Sheet steel material, Door needs to be added seperately, Door can be mounted Left or Right, Door opening 135°, Backplate sheet steel, Top and Bottom need to be added sepretely, Cable entry by flange of big Cable entry, dimensions in mm (H x W x D) 1000 x 400 (384) x 250, No.Mod.DIN 72 (H=150 mm), prepared for extention side-by-side, prepared for interior fitting System pro E energy Combi (up to 800A) |

Technique

| | |
|---------------------------|---|
| Courant nominal (I_n) | 800 A |
| Power Loss | $\Delta t = 25K$ 45 W $\Delta t = 30K$ 65 W $\Delta t = 35K$ 86 W $\Delta t = 40K$ 107 W |
| Number of Flange Openings | 2 |
| Number of Rows | 6 |
| Cover Plate Type | Optional |

| | |
|---------------------|-----------------------|
| Type de montage | Surface mounting |
| Door Type | Single |
| Finition de surface | Powder coating |
| Qualité du matériau | Steel |
| RAL Number | RAL 7035 - Gris clair |
| Couleur | Grey |
| Nombre de batteries | 0 |

Environnement

| | |
|---|--|
| Indice de protection | IP55 |
| Classe de protection | Grounded (Class I) |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 1STC860120 9AKK108467A5062 |
| REACH Declaration | 1STE000078 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|---|---|
| Width in Number of Modular Spacings | 12 |
| Produit Largeur Net | 396 mm |
| Produit Hauteur Net | 1049 mm |
| Produit Longueur Net | 250 mm |
| Poids net | 15.996 kg |
| Profondeur d'encastrement (t ₂) | 230 mm |
| Thickness | Cabinet Plate 1.5 mm Door Plate 1.5 mm |

Commande

| | |
|---------------------------|-------------|
| Emballage Niveau 1 Unités | box 1 pièce |
| Emballage Niveau 1 Poids | 18.6 kg |

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|------------|
| Déclaration de Conformité - CE | 1STC860120 |
|--------------------------------|------------|

Installation

| | |
|-------------------------|--------------------|
| Instructions et manuels | No document needed |
|-------------------------|--------------------|

Downloads Préférés

| | |
|--|--------------------|
| Fiche produit, informations techniques | No document needed |
|--|--------------------|

Building Information
Modeling - BIM

9AKK107680A9001

Classifications

| | |
|-----------------------------------|---------------------------|
| ETIM 8 | EC000058 - Empty cabinet |
| ETIM 9 | EC000058 - Empty cabinet |
| Catégorie DEEE | Product Not in WEEE Scope |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85381000 |
| eClass | V11.0 : 27142408 |
| Code de classification d'objet | U |

Catégories

Produits basse tension → Tableaux, Coffrets et Armoires → Tableaux Divisionnaires → Sub Distribution Boards → System pro E energy M

