

PRODUCT-DETAILS

AS16-30-10S-20

AS16-30-10S-20 24V50/60HZ Contactor



Informations générales

Extension du type de produit	AS16-30-10S-20
Code de produit	1SBL121004R2010
EAN	3471523042209
Description courte	AS16-30-10S-20 24V50/60HZ Contactor

Description longue	<p>AS16 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. The AS..S contactors are the spring terminal version of the AS... range. The AS... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front-mounted add-on auxiliary contact blocks (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.</p>
--------------------	--

Commande

Quantité minimum	40 pièce
Code douanier	85364900

Downloads Préférés

Instructions et manuels	1SBC101020M9701
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Produit Largeur Net	45 mm
Produit Longueur Net	72.5 mm
Produit Hauteur Net	68 mm
Poids net	0.22 kg

Technique

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	0
Normes et standards	IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1, UL 508, CSA C22.2 N° 14
Tension	Circuit auxiliaire 690 V Circuit principal 690 V
Fréquence assignée (f)	Circuit auxiliaire 50 / 60 Hz Circuit principal 50 / 60 Hz
Courant thermique conventionnel à l'air libre (I_{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 22 A acc. to IEC 60947-5-1, $\Theta = 40\text{ °C}$ 10 A
Courant assignée d'emploi AC-1 (I_e)	(690 V) 40 °C 22 A (690 V) 60 °C 17 A (690 V) 70 °C 14 A
Courant assignée d'emploi AC-3 (I_e)	(415 V) 60 °C 15.5 A (440 V) 60 °C 13.6 A (500 V) 60 °C 12.5 A (690 V) 60 °C 9 A (380 / 400 V) 60 °C 15.5 A (220 / 230 / 240 V) 60 °C 15.7 A
Puissance assignée d'emploi AC-3 (P_e)	(400 V) 7.5 kW (415 V) 7.5 kW (440 V) 7.5 kW (500 V) 7.5 kW (690 V) 7.5 kW (220 / 230 / 240 V) 4 kW
Courant assignée d'emploi AC-15 (I_e)	(500 V) NC 2 (500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Courant assigné de courte durée admissible (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 124 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 22 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 55 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 250 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 75 A for 0.1 s 140 A

	for 1 s 100 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 155 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 90 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-15) 1200 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour (DC-13) 900 cycles per hour
Courant assignée d'emploi DC-13 (I _g)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W
Tension assignée d'isolement (U _i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Tension assignée de tenue aux chocs (U _{imp})	Circuit auxiliaire 6 kV
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U _c)	50 Hz 24 V 60 Hz 24 V
Durée de fonctionnement nominale	Entre la mise hors tension de la bobine et la fermeture du contact NC (normally closed) 7 ... 22 ms Entre la mise hors tension de la bobine et l'ouverture du contact NO (normally open) 5 ... 19 ms Entre la mise sous tension de la bobine et l'ouverture du contact NC 6 ... 18 ms Entre la mise sous tension de la bobine et la fermeture du contact NO 9 ... 24 ms
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 0.75 ... 1.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 0.75 ... 1.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 0.75 ... 1.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ²
Wire Stripping Length	Auxiliary Circuit 10 mm Control Circuit 10 mm Main Circuit 10 mm
Indice de protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 IP20
Type de borne	Spring Terminals

Technique UL/CSA

General Use Rating UL/CSA	(600 V AC) 15.2 A
Puissance nominale UL/CSA	(120 V AC) Single Phase 3/4 hp (200 ... 208 V AC) Three Phase 3 hp (220 ... 240 V AC) Three Phase 5 hp (240 V AC) Single Phase 2 hp (440 ... 480 V AC) Three Phase 10 hp (550 ... 600 V AC) Three Phase 10 hp

Environnement

Température de l'air ambiant	Close to Contactor Fitted with Thermal O/L Relay -25 ... 60 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Altitude de fonctionnement maximale autorisée	Without Derating 3000 m
REACH Declaration	2CMT2021-006202
Résistance aux chocs selon CEI 60068-2-27	Closed, Shock Direction: B1 10 g Closed, Shock Direction: C1 20 g Closed, Shock Direction: C2 20 g Open, Shock Direction: B1 5 g Open, Shock Direction: C1 9 g Open, Shock Direction: C2 14 g Shock Direction: A 20 g Shock Direction: B2 15 g
Resistance to Vibrations acc. to IEC 60068-2-6	5 ... 300 Hz 3 g Closed position / 2 g Open position
Informations RoHS	2CMT2021-006277
Statut RoHS	Following EU Directive 2011/65/EU

Certificats et Déclarations (Numéro de document)

CB Certificate	CB_CN13475-M1
CCC Certificate	CCC_2007010309251577
CQC Certificate	CQC2007010309251577
Declaration of Conformity - CCC	2020980304001224
Déclaration de Conformité - CE	1SBD250014U1000
Declaration of Conformity - UKCA	1SBD250049U1000
Certificat GOST	GOST_POCCCNME77B07822.pdf
Certificat UL	UL_20120917_E312527_1_1
UL Listing Card	UL_E312527

Emballage

Emballage Niveau 1 Unités	1 pièce
Emballage Niveau 1 Largeur	78 mm
Emballage Niveau 1 Longueur	80 mm
Emballage Niveau 1 Hauteur	48 mm
Emballage Niveau 1 Poids	0.22 kg
Emballage Niveau 1 EAN	3471523042209
Emballage Niveau 2 Unités	40 pièce

Emballage Niveau 2 Largeur	250 mm
Emballage Niveau 2 Longueur	195 mm
Emballage Niveau 2 Hauteur	315 mm
Emballage Niveau 2 Poids	8.8 kg
Emballage Niveau 3 Unités	960 pièce

Classifications

Code de classification d'objet	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - contacteur de puissance pour commutation de courant alternatif
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
Code de catégorie granulaire IDEA (IGCC)	4761 >> Magnet contactor, AC-switching

Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Contacteurs → Contacteurs monoblocs → AS
Contactors → AS16

