

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED
Emission: DIRECT
Optics: LENTI UGR<18
Colour: WHITE
Dimming: ON/OFF
Emergency: WITH ACCESSORY
L: 595mm
A: 595mm
H: 14 (30 con driver)mm
Warranty: 5 years
Weight: 3.4kg

Tech data

Luminaire input power: 34W
Luminaire luminous flux: 4000lm
Luminous flux in emergency: 1h: 13% / 3h: 5
IP: 40
Insulation class: II
Supply voltage: 900mA driver incluso
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 30W
Source luminous flux: 4895lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[View more product info](#)


SCHOOL

104129.01

novalux


ITALIAN LIGHTING DESIGN SINCE 1948

MOUNTING ACCESSORIES




SCHOOL: KIT INST.PLAFONE 600X600

104108.01



SCHOOL: KIT MOLLE PER INCASSO

104107.99




SCHOOL: KIT SOSPENSIONE H1200

104110.99



KIT ALIMENTAZIONE L1200 3P BIA

108919.01



THE PANEL 2: KIT INST.INC.RAS.CART.600

102028.99



SCHOOL: KIT ANTICADUTA L=3000


104119.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH


This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.

EMERGENCY ACCESSORIES



THE PANEL 2: EMER.INC.1H 10/54VDC

1020A4.99



THE PANEL 2: EMER.INC.3H 10/54VDC

1020A5.99