
ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 - 0 - 2. WITHDRAL AT 1



Product designation				Selector switch actuator key - 3 position
Product type designation				LPFS33
General characteristics				
Colour				Black
Type of positions				Selector switch
Material				Aluminium and zinc alloy for the metal part, polyamide for plastic parts
IEC degree of protection	on			IP66, IP67 and IP69K
Mechanical features				
Mechanical life			cycles	1000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120M
UL technical data				
UL degree of protection	n			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			_
		min	°C	-40
		max	°C	+85
Dimensions				



Certifications and compliance

Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 UL508

Certificates

1/2





ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 - 0 - 2. WITHDRAL AT 1

cULus

ETIM classification

ETIM 8.0 EC002611 - Control switch