

PRODUCT-DETAILS

# CL2-515Y

## CL2-515Y Pilot Light



### Informations générales

|                              |   |
|------------------------------|---|
| Extension du type de produit | CL2-515Y  |
| Code de produit              | 1SFA619403R5153   |
| EAN                          | 7320500556306   |
| Description courte           | CL2-515Y Pilot Light  |
| Description longue           | The CL2-515Y Pilot Light is: Compact - Pilot Light - Pilot light head - Yellow - Illuminated - 110 ... 130 V<br>This Pilot Light is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost.<br>The compact range has a high level of dust and water resistance. |

### Commande

|                  |            |
|------------------|------------|
| Quantité minimum | 10 pièce   |
| Code douanier    | 8536619090 |

### Downloads Préférés

|  |                 |
|--|-----------------|
| Fiche produit, informations techniques | 1SFC151007C02_  |
| Instructions et manuels                | 1SFC151011M0201 |

---

**Dimensions**


---

|                      |          |
|----------------------|----------|
| Produit Largeur Net  | 0.03 m   |
| Produit Hauteur Net  | 0.03 m   |
| Produit Longueur Net | 0.052 m  |
| Poids net            | 0.018 kg |

---



---

**Technique**


---

|                              |  |
|------------------------------|--|
| Température de l'air ambiant | Operation -25 ... +70 °C<br>Storage -40 ... +85 °C   |
| Couleur                      | Yellow   |
| Actuator Type                | Pilot light head   |
| Voyant                       | Illuminated  |
| Type de lampe                | 110-130 V DC, integrated LED   |
| Indice de protection         | Front IP66<br>Front IP67<br>Front IP69K<br>Terminals IP20  |
| Classe de protection (NEMA)  | Type1<br>Type12<br>Type13<br>Type3R<br>Type4<br>Type4X   |
| Degré de pollution           | 3  |
| Tension                      | Supply Circuit 110 ... 130 V DC  |
| Connecting Capacity          | Flexible with Ferrule 1 x 0.75...2.5 mm <sup>2</sup><br>Flexible with Ferrule 2 x 0.75...2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1 x 0.75...2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2 x 0.75...2.5 mm <sup>2</sup><br>Flexible 1 x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible 2 x 0.75 ... 2.5 mm <sup>2</sup><br>Solid 1 x 0.75...2.5 mm <sup>2</sup><br>Solid 2 x 0.75...2.5 mm <sup>2</sup> |
| Type de raccordement         | Screw Clamp  |
| Type de borne                | Screw Terminals  |
| Couple de serrage            | 0.9 N·m  |
| Wire Stripping Length        | 8 mm   |

---



---

**Technique UL/CSA**


---

|                     |                |
|---------------------|----------------|
| Connecting Capacity | 1x 18...14 AWG |
| UL/CSA              | 2x 18...14 AWG |

---



---

**Environnement**


---

|   |  |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658  |
| Informations RoHS                           | 2CMT2015-005451  |
| Statut RoHS                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| WEEE B2C / B2B                              | Business To Business   |
| Catégorie DEEE                              | 5. Small Equipment (No External Dimension More Than 50 cm)             |

---



---

**Certificats et Déclarations (Numéro de document)**


---

|                |                |
|----------------|----------------|
| CB Certificate | CQC_CN_CN50749 |
|----------------|----------------|

|                                     |                             |
|-------------------------------------|-----------------------------|
| CQC Certificate                     | CQC2003010305054693         |
| Certificat ecULus                   | UL_E496500-20171020         |
| cURus Certificate                   | UL_E496500-20171020         |
| Declaration of Conformity<br>- CCC  | 2020980305001187            |
| Déclaration de Conformité<br>- CE   | 2CMT2015-005451             |
| Declaration of Conformity<br>- UKCA | 2CMT2020-006121             |
| DNV GL Certificate                  | 9AKK107046A3749             |
| EAC Certificate                     | EAC-RU C-CN.ME77.B.00690_20 |

## Emballage

|                                |               |
|--------------------------------|---------------|
| Emballage Niveau 1<br>Unités   | bag 10 pièce  |
| Emballage Niveau 1<br>Largeur  | 0.235 m       |
| Emballage Niveau 1<br>Longueur | 0.125 m       |
| Emballage Niveau 1<br>Hauteur  | 0.035 m       |
| Emballage Niveau 1 Poids       | 0.184 kg      |
| Emballage Niveau 1 EAN         | 7320500475607 |

## Classifications

|   |  |
|---|--|
| Code de classification<br>d'objet           | P  |
| ETIM 6                                      | EC000272 - voyant lumineux, appareil complet |
| ETIM 7                                      | EC000272 - Indicator light complete          |
| ETIM 8                                      | EC000272 - Indicator light complete          |
| eClass                                      | V11.0 : 27371223                             |
| UNSPSC                                      | 39121534                                     |
| Code de catégorie<br>granulaire IDEA (IGCC) | 4766 >> Indicator or pilot lights            |
| E-Number (Finland)                          | 2313539                                      |
| E-Number (Norway)                           | 4373527                                      |
| E-Number (Sweden)                           | 3705768                                      |

## Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Unités de commande et de signalisation → Compact Range → CL Compact Pilot Lights

Produits et Systèmes Moyenne Tension → Service → Pièces détachées → Parts → All Spare Parts (Relays-SWG-CB)

