SELECTOR SWITCH ACTUATOR KEY Ø22MM PLATINUM SERIES CHROMED PLASTIC, 3 POSITION, 1 - 0 - 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 1



Product designation Product type designatio	on			Selector switch actuator key - 3 position LPCS33
General characteristics				
Colour				Black
Type of positions				Selector switch
Material				Polyamide
IEC degree of protection	on			IP66, IP67 and IP69K
Mechanical features				
Mechanical life			cycles	1000000
Mounting adapter				LPXAU120
Weight			g	60
UL technical data				
UL degree of protection	1			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			
		min	°C	-40
		max	°C	+85

25.2 (0.99") (0.88")

Certifications	and	compliance
Compliance		

• • · · · · • · · · · · · · ·	
	CSA C22.2 n° 14

IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1

UL508

Certificates

Dimensions

CCC

cULus





SELECTOR SWITCH ACTUATOR KEY Ø22MM PLATINUM SERIES CHROMED PLASTIC, 3 POSITION, 1 - 0 - 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 1

ETIM classification

ETIM 8.0

EC000222 -Front element for selector switch