STRIP LED

100916.99











SMD 2835 (336 LED/m) Biadesivo - sezionabile ogni 41,6 mm (14 LED) Biadhesive - cuttable every 41,6 mm (14 LED)

Features

Use: Indoor

Dimming: WITH ACCESSORY **Emergency: WITH ACCESSORY**

L: 5000mm A: 24mm

Warranty: 5 years Weight: 0.15kg

Tech data

Luminous flux in emergency: L min = 20 L max = 100 - 1h: 17% / 3h: 7%

IP: 20

Insulation class: III Supply voltage: 24 Vdc Energy efficiency class: F

SELV: No

Source

Light source: LED Source power: 25W/m Source luminous flux: 2926lm Colour temperature: 2700K

CRI: >90

LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

View more product info



STRIP LED

100916.99



EMERGENCY ACCESSORIES



KIT EMERGENZA 3H 10V-54V

18005.99



KIT EMERGENZA 1H 10V-54V

18004.99

