

PRODUCT-DETAILS

6867 AGM-208-500

Outdoor Movement Detector MasterLINE

Remote control silver metallic



Informations générales

| | |
|------------------------------|---|
| Extension du type de produit | 6867 AGM-208-500 |
| Code de produit | 2CKA006800A2555 |
| EAN | 4011395150894 |
| Description courte | Outdoor Movement Detector MasterLINE Remote control silver metallic |

| | |
|--------------------|---|
| Description longue | <p>Electronic movement detector for detecting thermal motion. Remote control possible via IR remote control 6841-101 (included in scope of delivery). Remote configurable via IR service remote control 6842-101. With display for detection and operation mode. With ground and rear-field detection. With high-quality lens for optimum detection. Detection sensitivity adjustable via IR service remote control. Surveillance density: 110 sectors with 440 switching segments. With integrated dismantling protection. All functions controlled by microprocessor. Always-On (4 hours) and Presencesimulation can be activated via IR-remote control. Reading in the current brightness value as switching threshold via remote control. With automatic range stabilization. With automatic interference suppression. With automatic dazzle-proofing. With brightness-independent test mode for evaluating the detection zone. Individual adjustment of detection range via enclosed protective foil which can be cut to size. Additional possibility for switch-on via normally open push-button switch. Switch-off delay: 10 sec to 30 min or short-time pulse 1 sec adjustable.</p> |
|--------------------|---|

Installation

| | |
|-------------------------|-------------------|
| Instructions et manuels | DEBJE-0073-1-8054 |
|-------------------------|-------------------|

Technique

| | |
|--|--|
| Fiche produit, informations techniques | No document needed |
| Tension nominale (U_r) | 230 V |
| Auxiliary Voltage AC/DC | 230 V AC/DC |
| Type de tension | AC |
| Courant nominal (I_n) | 16 A |
| Current Range | Maximum 80 A Minimum 0.01 A |
| Fréquence (f) | 50...60 Hz |
| Fréquence assignée (f) | 50 ... 60 Hz |
| Maximum Switching Power | 3680 W |
| Power Loss | 1 W |
| Plage de mesure | Diameter Detection range on floor 32 m |
| Nombre de sorties | 1 |
| Number of Switching Zones | 1 |
| Conception | MasterLINE |
| Minimum Switching Time | Switch-On 10 second [unit of time] |
| Type de raccordement | Cable Clamp |
| Type de charge | ohmic, capacitive and inductive loads |
| Type de montage | Surface Mounted |
| Sensor Type | Passive infrared |
| Finition de surface | Surface protection: Untreated Surface finishing: Matt |
| Matériau | Thermoplastic |
| Comprend | Remote control |
| Type d'encastrement | wall |
| Flux lumineux | 0 ... 1000 lx |
| Model Number | Movement sensor |
| Couleur | silver metallic |
| Composition chimique de la batterie | Lithium |
| Désignation des dimensions | CR2025 |
| Type de batterie | Pile bouton |
| Poids de la batterie | 2 g |
| Nombre de batteries | 1 |
| Application Function | Electrical Load and Light Control |

Environnement

| | |
|------------------------------|--|
| Température de l'air ambiant | Operation -25 ... +55 °C |
| Indice de protection | IP55 |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 2CKA200000E6407 |

| | |
|---|-----------------|
| REACH Declaration | 2CKA309999E9999 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Dimensions

| | |
|---|---------|
| Produit Largeur Net | 125 mm |
| Produit Hauteur Net | 115 mm |
| Produit Longueur Net | 141 mm |
| Poids net | 0.54 kg |
| Profondeur d'encastrement (t ₂) | 0 mm |

Commande

| | |
|------------------------|-------------|
| ID du produit remplacé | 6800-0-2555 |
|------------------------|-------------|

Certificats et Déclarations (Numéro de document)

| | |
|--------------------------------|-----------------|
| Déclaration de Conformité - CE | 2CKA100000E2023 |
|--------------------------------|-----------------|

Classifications

| | |
|----------------|--|
| ETIM 8 | EC000133 - Movement sensor complete |
| ETIM 9 | EC000133 - Movement sensor/presence detector complete |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 8536 50 80 |
| eClass | V11.0 : 27144007 |

Accessories

| Identifiant | Description | Type | Quantity | Unit Of Measure |
|-----------------|----------------------------|------|----------|-----------------|
| 2CKA006899A0231 | RC suppressor 2 pole 230 V | 6899 | 1 | piece |

Catégories

Produits basse tension → Wiring Accessories - StandAlone Electronics → Outdoor Movement Detector → Professional Series

