

Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: CAFFE
Dimming: PUSH, DALI
Emergency: NO
L: 800mm
A: 38mm
H: 65mm
Made in: ITALY
Warranty: 5 years
Weight: 1.5kg

Tech data

Luminaire input power: 14.6W
Luminaire luminous flux: 1114lm
IP: 40
Insulation class: I
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 12W
Source luminous flux: 1934lm
Colour temperature: 3000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)

LUCKY MINI

103526.20

novalux

ITALIAN LIGHTING DESIGN SINCE 1948

SCREENS



LUCKY MINI: DIFF. OPALE L=6500


103507.99



LUCKY MINI: DIFF. OPALE PER L800

103510.99

COMPLETION ACCESSORIES



4x

KIT GIUNZIONE MODULI P-30/LUCKY MINI


103317.99



LUCKY MINI: COPPIA TESTATE CAFFEA

103509.20

MOUNTING ACCESSORIES



KIT ALIMENTAZIONE L3000 5P CAF

108922.20




LUCKY MINI: CAVO DI SOSPENSIONE L=3000

103513.99




Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.




ALL-TRACK: COPPIA ADATT. 3P+DALI NER

106723.02



ALL-TRACK: COPPIA ADATT. 3P+DALI BIA

106723.01



KIT ALIMENTAZIONE L1200 5P CAF

108921.20