

## YF2A24-100UW5XLEAX

Sensor/actuator cable

**PLUG CONNECTORS AND CABLES** 



### YF2A24-100UW5XLEAX | Sensor/actuator cable

PLUG CONNECTORS AND CABLES



### Ordering information

Туре	Part no.
YF2A24-100UW5XLEAX	2116868

Other models and accessories -> www.sick.com/Sensor\_actuator\_cable



### Detailed technical data

#### Technical specifications

Connection type head A	Female connector, M12, 4-pin, straight, A-coded
Connection type head B	Flying leads
Locking plug connector	Screw connection
Connector material	TPU
Connector color	Black
Locking nut material	Zinc die-cast, nickel-plated
Seal material	FKM
Tightening torque	0.6 Nm
Width across flats	13
Cable	10 m, 4-wire, PUR, halogen-free
Jacket material	PUR, halogen-free
Jacket color	Black
Conductor cross section	0.34 mm <sup>2</sup>
Shielding	Shielded
Bending radius	
Flexible use	> 7.5 x cable diameter
Stationary position	> 5 x cable diameter
<b>.</b> .	> 7.5 x cable diameter
Bending cycles	≤ 10,000,000
Nominal voltage, cable	300 V AC
Test voltage, cable	2,000 V AC
Reference voltage	
	60 V AC
	60 V DC
Rated impulse voltage	1.5 kV
Current loading	≤ 4 A
Traversing speed	3.3 m/s
Travelling distance	5 m

# YF2A24-100UW5XLEAX | Sensor/actuator cable PLUG CONNECTORS AND CABLES

Acceleration	≤ 5 m/s²
Signal type	Sensor/actuator cable
Torsion force	180°/1m
Torsion cycles	10,000,000
Cycles per minutes	60
Application	Drag chain operation Robot Robot
Authorizations	CE UL
UL File No.	E335179
Enclosure rating	IP65 / IP66K / IP67
Operating temperature	
Flexible use	-30 °C +105 °C
Stationary position	-40 °C +105 °C
Drag chain operation	-30 °C +105 °C
Head	-25 °C +85 °C
Contamination rating	3
Insulation resistance	> 100 MΩ
Overvoltage category	III
Specific insulation resistance	< 30 mΩ
Thermal resistance, piping	Flame retardant according to UL 1581 VW1 / CSA FT1 / IEC 60332-1, IEC 60332-2-2


### Classifications

ECLASS 5.0	19030312
ECLASS 5.1.4	19030312
ECLASS 6.0	27060304
ECLASS 6.2	27060304
ECLASS 7.0	27060304
ECLASS 8.0	27060304
ECLASS 8.1	27060304
ECLASS 9.0	27060304
ECLASS 10.0	27060304
ECLASS 11.0	27060304
ECLASS 12.0	27060304
ETIM 5.0	EC000830
ETIM 6.0	EC000830
ETIM 7.0	EC003249
ETIM 8.0	EC003249
UNSPSC 16.0901	26121604

### YF2A24-100UW5XLEAX | Sensor/actuator cable

PLUG CONNECTORS AND CABLES

Dimensional drawing (Dimensions in mm (inch))



## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

### WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

