

PRODUCT-DETAILS

# RB121G-115VUC

## RB121G-115VUC Interface relay R600 1c/o,A1-A2=115VAC/DC,5-250VAC/10mA-6A



### Informations générales

Extension du type de produit	RB121G-115VUC
Code de produit	1SNA645007R0100
EAN	4013614507786
Description courte	RB121G-115VUC Interface relay R600 1c/o,A1-A2=115VAC/DC,5-250VAC/10mA-6A

Description longue	<p>The RB121G-115VUC is a boxed interface relay with screw terminals, which can be seamlessly snap-on mounted onto a DIN Rail. The relay is soldered into device housing, ensuring a high resistance against vibration. This relay operates with a 115 V AC/DC rated control supply voltage and has a 1 c/o (SPDT) output with gold-plated contacts rated at 250 V / 6 A. This 6mm wide boxed interface relay may be used for electrical isolation, amplification and signal matching and enables the switching of high currents on a small footprint. It has an integrated LED, which provides the visual indication of the energization of the relay coil and UL 94-V0 certified device housing, improving safety by providing high levels flame retardation. Jumper bars are available as accessories.</p>
--------------------	---

### Commande

EAN	4013614507786
Quantité minimum	10 pièce
Code douanier	85364900

---

## Downloads Préférés

---

Fiche produit, informations techniques	2CDC110004C0210_05
Instructions et manuels	1SVC645000M9000
CAD Dimensional Drawing	2CDC001079B0201

---



---

## Dimensions

---

Produit Largeur Net	6 mm
Produit Hauteur Net	67.5 mm
Produit Longueur Net	70 mm
Poids net	0.02 kg

---



---

## Technique

---

Fonction	Boxed interface relay R600
Sub-Function	Relay with built in LED
Rated Control Supply Voltage (U <sub>s</sub> )	115 V AC/DC
Sortie	1 c/o (SPDT) contact
Output Signal	5 ... 250VAC / 10mA ... 6A
Type de borne	Screw Terminals
Indice de protection	IP20
Normes et standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60947-5-1 UL 508

---



---

## Environnement

---

Informations RoHS	1SVD982016-0001
Statut RoHS	Following EU Directive 2011/65/EU

---



---

## Certificats et Déclarations (Numéro de document)

---

CB Certificate	CB_DK-53188-UL
CCC Certificate	CCC_2017010303941444
CQC Certificate	CQC_2017010303941444
Certificat CSA	CSA_254821
cUR Certificate	cUR_E352056
Declaration of Conformity - CCC	CCC_2020980303000254
Déclaration de Conformité - CE	1SVD982016-0001
Declaration of Conformity - UKCA	1SVD982016-1000
EAC Certificate	EAC_RU_C-FR.ME77.B.01634

Certificat LR	LR_16_20068
UR Certificate	UR_E352056

## Emballage

Emballage Niveau 1 Unités	box 10 pièce
Emballage Niveau 1 Largeur	73 mm
Emballage Niveau 1 Longueur	80 mm
Emballage Niveau 1 Hauteur	71 mm
Emballage Niveau 1 Poids	0.23 kg
Emballage Niveau 1 EAN	3472596450076

## Classifications

Code de classification d'objet	K
ETIM 7	EC001437 - Switching relay
ETIM 8	EC001437 - Switching relay
ETIM 9	EC001437 - Switching relay
eClass	V11.0 : 27371601
UNSPSC	39122331

## Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Relais électroniques → Relais et optocoupleurs d'interface

